

Series: LKRA-VMA, BKRA-VMA

Light duty swivel and fixed castors with bolt hole fitting, heavy brackets

 75 - 120 kg



Brackets: LKRA/BKRA Series - Pressed steel, swivel bracket with double ball bearing in the swivel head, strong central kingpin, bolted wheel axle, zinc-plated.
Detailed description: Page 60 and 76.

Wheels: Tyres: Type VMA 125 and VMA 126: Solid rubber tyres, colour grey, non-marking, 80° shore A. Type VMA 127: Two-component solid rubber tyre, colour grey, non-marking, 70° shore A, low starting and rolling resistance, high operational comfort. Rims: Made of high-quality nylon, colour grey, plain or ball bearing.
Particularly suitable for medical-technical applications.

Detailed description: Page 100 and 31.

Swivel castors	Fixed castors	Swivel castors with "stop-fix" brake	Wheel Ø [mm]	Tyre width [mm]	Load capacity [kg]	Bearing version	Total height [mm]	Plate Ø [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
Ref. No.	Ref. No.	Ref. No.								
LKRA-VMA 125G	BKRA-VMA 125G	LKRA-VMA 125G-FI	125	25	75	Plain bearing	158	57	13	40
LKRA-VMA 125G-11		LKRA-VMA 125G-11-FI	125	25	75	Plain bearing	158	57	11	40
LKRA-VMA 126G	BKRA-VMA 126G	LKRA-VMA 126G-FI	125	32	110	Plain bearing	158	57	13	40
LKRA-VMA 126G-11		LKRA-VMA 126G-11-FI	125	32	110	Plain bearing	158	57	11	40
LKRA-VMA 127K	BKRA-VMA 127K	LKRA-VMA 127K-FI	125	33	120	Ball bearing	158	57	13	40
LKRA-VMA 127K-11		LKRA-VMA 127K-11-FI	125	33	120	Ball bearing	158	57	11	40

