

Series: LKPA-PTH, BKPA-PTH

**Light duty swivel and fixed castors, heavy brackets**

120 kg



3

Further information on the internet: [www.blickle.de](http://www.blickle.de)




**Brackets:** LKPA/BKPA Series - Pressed steel, swivel bracket with double ball bearing in the swivel head, strong central kingpin, bolted wheel axle, zinc-plated.  
Top plate drawings: Page 70.  
Detailed description: Page 60 and 76.

**Wheels:** PTH Series - Treads: Made of injection-moulded polyurethane, colour grey, non-marking, 98° shore A, abrasion-resistant, non-staining, floor-saving, low-noise operation, low rolling resistance, excellent positive and non-positive connection with the wheel centre.  
Wheel centres: Made of high-quality nylon, colour light grey, shock and impact-resistant, corrosion-resistant, plain or ball bearing.  
Detailed description: Page 102 and 32.

Swivel castors	Fixed castors	Swivel castors with "stop-fix" brake
----------------	---------------	--------------------------------------

Ref. No.	Ref. No.	Ref. No.	Wheel Ø [mm]	Wheel width [mm]	Load capacity [kg]	Bearing version	Total height [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
LKPA-PTH 80G	BKPA-PTH 80G	LKPA-PTH 80G-FI	80	30	120	Plain bearing	111	90 x 66	75x45/61x51	8,5	40
LKPA-PTH 101G	BKPA-PTH 101G	LKPA-PTH 101G-FI	100	30	120	Plain bearing	136	90 x 66	75x45/61x51	8,5	40
LKPA-PTH 101K	BKPA-PTH 101K	LKPA-PTH 101K-FI	100	30	120	Ball bearing	136	90 x 66	75x45/61x51	8,5	40
LKPA-PTH 126G	BKPA-PTH 126G	LKPA-PTH 126G-FI	125	30	120	Plain bearing	161	90 x 66	75x45/61x51	8,5	40
LKPA-PTH 126K	BKPA-PTH 126K	LKPA-PTH 126K-FI	125	30	120	Ball bearing	161	90 x 66	75x45/61x51	8,5	40



**Variants / Accessories**



	Antistatic version, non-marking grey	With pressed steel thread guard, zinc-plated
Technical description page	32	79
Ref. No. extension	-ELS	-FA
Available for wheel Ø [mm]	Upon request	All sizes