

Series: LRA-POA  
**Light duty swivel castors with bolt hole fitting**

75 kg



3


Further information on the internet: [www.blickle.de](http://www.blickle.de)



**Brackets:** LRA Series - Pressed steel, with double ball bearing in the swivel head, bolted wheel axle, zinc-plated.  
Detailed description: Page 59 and 76.

**Wheels:** POA Series - Made of high-quality nylon, colour black, high abrasion resistance, low rolling resistance, smooth running performance on even floors, shock and impact-resistant, corrosion-resistant, high chemical resistance to alcohol, salts, greases and certain acids and lyes in diluted concentration, plain bearing.  
Detailed description: Page 107 and 32.

Swivel castors		Swivel castors with "stop-fix" brake		Wheel Ø	Wheel width	Load capacity	Bearing version	Total height	Plate Ø	Bolt hole Ø	Offset
Ref. No.	Ref. No.	[mm]	[mm]	[kg]	[mm]	[mm]		[mm]	[mm]	[mm]	[mm]
LRA-POA 35G		35	25	75	Plain bearing	50	43	11	15		
LRA-POA 50G	LRA-POA 50G-FI	50	18	75	Plain bearing	69	43	11	25		
LRA-POA 75G	LRA-POA 75G-FI	75	23	75	Plain bearing	98	43	11	28		



**Variants / Accessories**

	With threaded pin M10 x 30	With plug-in pin 11 x 30,5	Synthetic castor sockets for round tubes	With metal expander fitting
Technical description page	74	75	75	75
Ref. No. extension	-GS10	-ES	See below	See below
Available for wheel Ø [mm]	All sizes	All sizes	All swivel castors with plug-in pin	All sizes

**Metal expander fitting**

Internal tube dim. round tube [mm]	Internal tube dim. square tube [mm]	Ref. No. extension
17 - 19	17 - 19	-E01
20 - 25	18 - 21	-E02
25 - 30	21 - 25	-E03
30 - 35	25 - 29	-E04
35 - 40	29 - 32	-E05
39 - 45	32 - 38,5	-E07

**Synthetic castor socket**

Ref. No.	Internal tube dim. round tube [mm]	Flange dimension Ø x height [mm]	Total length castor socket [mm]
RHR 20-18/11A	Ø 18,0	Ø 20,0 x 5,0	42
RHR 22-19/11A	Ø 19,0	Ø 22,0 x 5,0	42
Further dimensions upon request			