

Series: LKRA-POA

Light duty swivel castors with bolt hole fitting, heavy brackets

110 - 120 kg



3

Further information on the internet: www.blickle.de



Brackets: LKRA Series - Pressed steel, with double ball bearing in the swivel head, strong central kingpin, bolted wheel axle, zinc-plated.
Detailed description: Page 60 and 76.

Wheels: POA Series - Made of high-quality nylon, colour black, high abrasion resistance, low rolling resistance, smooth running performance on even floors, shock and impact-resistant, corrosion-resistant, high chemical resistance to alcohol, salts, greases and certain acids and lyes in diluted concentration, plain or ball bearing.
Detailed description: Page 107 and 32.

Swivel castors		Swivel castors with "stop-fix" brake		Wheel Ø	Wheel width	Load capacity	Bearing version	Total height	Plate Ø	Bolt hole Ø	Offset
Ref. No.	Ref. No.	[mm]	[mm]	[kg]				[mm]	[mm]	[mm]	[mm]
LKRA-POA 80G	LKRA-POA 80G-FI	80	33	120	Plain bearing	108	57	13	40		
LKRA-POA 80G-11	LKRA-POA 80G-11-FI	80	33	120	Plain bearing	108	57	11	40		
LKRA-POA 100G	LKRA-POA 100G-FI	100	32	120	Plain bearing	133	57	13	40		
LKRA-POA 100G-11	LKRA-POA 100G-11-FI	100	32	120	Plain bearing	133	57	11	40		
LKRA-POA 100K	LKRA-POA 100K-FI	100	30	120	Ball bearing	133	57	13	40		
LKRA-POA 100K-11	LKRA-POA 100K-11-FI	100	30	120	Ball bearing	133	57	11	40		
LKRA-POA 125G	LKRA-POA 125G-FI	125	32	120	Plain bearing	158	57	13	40		
LKRA-POA 125G-11	LKRA-POA 125G-11-FI	125	32	120	Plain bearing	158	57	11	40		
LKRA-POA 125K	LKRA-POA 125K-FI	125	30	120	Ball bearing	158	57	13	40		
LKRA-POA 125K-11	LKRA-POA 125K-11-FI	125	30	120	Ball bearing	158	57	11	40		
LKRA-POA 150G	LKRA-POA 150G-FI	150	32	110	Plain bearing	182	57	13	40		
LKRA-POA 150G-11	LKRA-POA 150G-11-FI	150	32	110	Plain bearing	182	57	11	40		

Variants / Accessories



	With threaded pin M12 x 30	With metal expander fitting
Technical description page	74	75
Ref. No. extension	-GS12	See below
Available for wheel Ø [mm]	All sizes	All with bolt hole Ø 11 mm

Metal expander fitting

Internal tube dim. round tube [mm]	Internal tube dim. square tube [mm]	Ref. No. extension
17 - 19	17 - 19	-E11
20 - 25	18 - 21	-E12
25 - 30	21 - 25	-E13
30 - 35	25 - 29	-E14
35 - 40	29 - 32	-E15
39 - 45	32 - 38,5	-E17