



Series: TPA
**Wheels with thermoplastic rubber tread,
 synthetic wheel centre**

50 - 140 kg

3

Further information on the internet: www.blickle.de



Treads: Made of thermoplastic rubber, colour grey, non-marking, 85° shore A.
Wheel centres: Made of polypropylene, colour light grey, colour black for "-ELS" version (refer to Variants / Accessories), plain or ball bearing.

As standard, ball bearing versions with wheel Ø of 50-125 mm are supplied with synthetic thread guards.

Wheels

Detailed description: Page 30.

Ref. No.	Wheel Ø (D) [mm]	Wheel width (T2) [mm]	Load capacity [kg]	Bearing version	Axle bore Ø (d) [mm]	Hub length (T1) [mm]
TPA 50/8G	50	19	50	Plain bearing	8	22
TPA 50/8K-FK	50	19	50	Ball bearing	6	23
TPA 75/8G	75	25	75	Plain bearing	8	29,5
TPA 75/8K-FK	75	25	75	Ball bearing	6	31
TPA 80/12G	80	32	90	Plain bearing	12	35
TPA 80/8K-FK	80	32	90	Ball bearing	8	36
TPA 100/8G	100	25	80	Plain bearing	8	29,5
TPA 101/12G	100	32	100	Plain bearing	12	35
TPA 101/8K-FK	100	32	100	Ball bearing	8	36
TPA 126/12G	125	32	110	Plain bearing	12	35
TPA 126/8K-FK	125	32	110	Ball bearing	8	36
TPA 150/12G	150	32	130	Plain bearing	12	36
TPA 150/12K	150	32	130	Ball bearing	12	33
TPA 200/12K	200	32	140	Ball bearing	12	33

Variants / Accessories



	Antistatic version, non-marking grey	With bearing seal for ball bearings
Technical description page	30	58
Ref. No. extension	-ELS	-KD
Available for wheel Ø [mm]	50 - 125	50 - 125

