

Series: LRA-TPA, BRA-TPA

Light duty swivel and fixed castors with bolt hole fitting

50 - 75 kg



Brackets: LRA/BRA Series - Pressed steel, swivel bracket with double ball bearing in the swivel head, bolted wheel axle, zinc-plated.
Detailed description: Page 59 and 76.

Wheels: TPA Series - Treads: Made of thermoplastic rubber, colour grey, non-marking, 85° shore A.
Wheel centres: Made of polypropylene, colour light grey, colour black for "-ELS" version (refer to Variants / Accessories), plain or ball bearing.

As standard, ball bearing versions are supplied with synthetic thread guards.

Detailed description: Page 84 and 30.

Swivel castors	Fixed castors	Swivel castors with "stop-fix" brake	Wheel Ø [mm]	Wheel width [mm]	Load capacity [kg]	Bearing version	Total height [mm]	Plate Ø [mm]	Bolt hole Ø [mm]	Offset swvl castor [mm]
LRA-TPA 50G	BRA-TPA 50G	LRA-TPA 50G-FI	50	19	50	Plain bearing	69	43	11	25
LRA-TPA 50K-FK	BRA-TPA 50K-FK	LRA-TPA 50K-FI-FK	50	19	50	Ball bearing	69	43	11	25
LRA-TPA 75G	BRA-TPA 75G	LRA-TPA 75G-FI	75	25	75	Plain bearing	98	43	11	28
LRA-TPA 75K-FK	BRA-TPA 75K-FK	LRA-TPA 75K-FI-FK	75	25	75	Ball bearing	98	43	11	28
LRA-TPA 100G		LRA-TPA 100G-FI	100	25	70	Plain bearing	121	43	11	33

3

Further information on the internet: www.blickle.de

Variants / Accessories



	Antistatic version, non-marking grey	With synthetic thread guard	With electrostatic powder coating	With threaded pin M10 x 30	With plug-in pin 11 x 30.5	Synthetic castor sockets for round tubes	With metal expander fitting
Technical description page	30	30 + 79		74	75	75	75
Ref. No. extension	-ELS	Standard		-GS10	-ES	See below	See below
Available for wheel Ø [mm]	All sizes	All ball bearing versions	Upon request	All swivel castors	All swivel castors	All swivel castors with plug-in pin	All swivel castors

Metal expander fitting

Internal tube dim. round tube [mm]	Internal tube dim. square tube [mm]	Ref. No. extension
17 - 19	17 - 19	-E01
20 - 25	18 - 21	-E02
25 - 30	21 - 25	-E03
30 - 35	25 - 29	-E04
35 - 40	29 - 32	-E05
39 - 45	32 - 38,5	-E07

Synthetic castor socket

Ref. No.	Internal tube dim. round tube [mm]	Flange dimension Ø x height [mm]	Total length castor socket [mm]
RHR 20-18/11A	Ø 18,0	Ø 20,0 x 5,0	42
RHR 22-19/11A	Ø 19,0	Ø 22,0 x 5,0	42
Further dimensions upon request			