

Series: LMDA-TPA

**Light duty twin wheel swivel castors with bolt hole fitting**

 80 - 100 kg




**Brackets:** LMDA Series - Pressed steel, with double ball bearing in the swivel head, bolted wheel axle, zinc-plated.  
Detailed description: Page 59 and 76.

**Wheels:** TPA Series - Treads: Made of thermoplastic rubber, colour grey, non-marking, 85° shore A.  
Wheel centres: Made of polypropylene, colour light grey, colour black for "-ELS" version (refer to Variants / Accessories), plain or ball bearing.

As standard, ball bearing versions are supplied with synthetic thread guards.

Detailed description: Page 84 and 30.

Swivel castors		Swivel castors with "stop-fix" brake		Wheel Ø	Wheel width	Load capacity	Bearing version	Total height	Plate Ø	Bolt hole Ø	Offset
Ref. No.	Ref. No.	[mm]	[mm]	[kg]	[mm]	[mm]		[mm]	[mm]	[mm]	[mm]
LMDA-TPA 50G	LMDA-TPA 50G-FI	50	2 x 19	80	Plain bearing	71	41	10,2	31		
LMDA-TPA 50K-FK	LMDA-TPA 50K-FI-FK	50	2 x 19	80	Ball bearing	71	41	10,2	31		
LMDA-TPA 75G	LMDA-TPA 75G-FI	75	2 x 25	100	Plain bearing	98	55	10,2	34		
LMDA-TPA 75K-FK	LMDA-TPA 75K-FI-FK	75	2 x 25	100	Ball bearing	98	55	10,2	34		



**Variants / Accessories**



	Antistatic version, non-marking grey	With synthetic thread guard
Technical description page	30	30 + 79
Ref. No. extension	-ELS	Standard
Available for wheel Ø [mm]	All sizes	All ball bearing versions