

Series: LDA-TPA

Light duty twin wheel swivel castors

 80 - 100 kg



3

Further information on the internet: www.blickle.de



Brackets: LDA Series - Pressed steel, double ball bearing in the swivel head, bolted wheel axle, zinc-plated.
Top plate drawings: Page 70.
Detailed description: Page 60 and 76.

Wheels: TPA Series - Treads: Made of thermoplastic rubber, colour grey, non-marking, 85° shore A.
Wheel centres: Made of polypropylene, colour light grey, colour black for "-ELS" version (refer to Variants / Accessories), plain or ball bearing.

As standard, ball bearing versions are supplied with synthetic thread guards.

Detailed description: Page 84 and 30.

Swivel castors		Swivel castors with "stop-fix" brake		Wheel Ø	Wheel width	Load capacity	Bearing version	Total height	Plate size	Bolt hole spacing	Bolt hole Ø	Offset
Ref. No.	Ref. No.	[mm]	[mm]	[kg]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]
LDA-TPA 50G	LDA-TPA 50G-FI	50	2 x 19	80	Plain bearing	71	60 x 60	38x38/48x48	6,2	31		
LDA-TPA 50K-FK	LDA-TPA 50K-FI-FK	50	2 x 19	80	Ball bearing	71	60 x 60	38x38/48x48	6,2	31		
LDA-TPA 75G	LDA-TPA 75G-FI	75	2 x 25	100	Plain bearing	101	60 x 60	40x40/46x46	6,2	34		
LDA-TPA 75K-FK	LDA-TPA 75K-FI-FK	75	2 x 25	100	Ball bearing	101	60 x 60	40x40/46x46	6,2	34		



Variants / Accessories



	Antistatic version, non-marking grey	With synthetic thread guard
Technical description page	30	30 + 79
Ref. No. extension	-ELS	Standard
Available for wheel Ø [mm]	All sizes	All ball bearing versions