

Series: LKPA-TPA, BKPA-TPA

**Light duty swivel and fixed castors, heavy brackets**

90 - 110 kg




**Brackets:** LKPA/BKPA Series - Pressed steel, swivel bracket with double ball bearing in the swivel head, strong central kingpin, bolted wheel axle, zinc-plated.  
Top plate drawings: Page 70.  
Detailed description: Page 60 and 76.

**Wheels:** TPA Series - Treads: Made of thermoplastic rubber, colour grey, non-marking, 85° shore A.  
Wheel centres: Made of polypropylene, colour light grey, colour black for "-ELS" version (refer to Variants / Accessories), plain or ball bearing.

As standard, ball bearing versions with wheel Ø of 80-125 mm are supplied with synthetic thread guards.

Detailed description: Page 84 and 30.

Swivel castors		Fixed castors		Swivel castors with "stop-fix" brake		Wheel Ø	Wheel width	Load capacity	Bearing version	Total height	Plate size	Bolt hole spacing	Bolt hole Ø	Offset swivel castor
Ref. No.	Ref. No.	Ref. No.	Ref. No.	Ref. No.	Ref. No.	[mm]	[mm]	[kg]		[mm]	[mm]	[mm]	[mm]	[mm]
LKPA-TPA 80G	BKPA-TPA 80G	LKPA-TPA 80G-FI		LKPA-TPA 80G-FI		80	32	90	Plain bearing	111	90 x 66	75x45/61x51	8,5	40
LKPA-TPA 80K-FK	BKPA-TPA 80K-FK	LKPA-TPA 80K-FI-FK		LKPA-TPA 80K-FI-FK		80	32	90	Ball bearing	111	90 x 66	75x45/61x51	8,5	40
LKPA-TPA 101G	BKPA-TPA 101G	LKPA-TPA 101G-FI		LKPA-TPA 101G-FI		100	32	100	Plain bearing	136	90 x 66	75x45/61x51	8,5	40
LKPA-TPA 101K-FK	BKPA-TPA 101K-FK	LKPA-TPA 101K-FI-FK		LKPA-TPA 101K-FI-FK		100	32	100	Ball bearing	136	90 x 66	75x45/61x51	8,5	40
LKPA-TPA 126G	BKPA-TPA 126G	LKPA-TPA 126G-FI		LKPA-TPA 126G-FI		125	32	110	Plain bearing	161	90 x 66	75x45/61x51	8,5	40
LKPA-TPA 126K-FK	BKPA-TPA 126K-FK	LKPA-TPA 126K-FI-FK		LKPA-TPA 126K-FI-FK		125	32	110	Ball bearing	161	90 x 66	75x45/61x51	8,5	40
LKPA-TPA 150G	BKPA-TPA 150G	LKPA-TPA 150G-FI		LKPA-TPA 150G-FI		150	32	110	Plain bearing	185	90 x 66	75x45/61x51	8,5	40
LKPA-TPA 150K	BKPA-TPA 150K	LKPA-TPA 150K-FI		LKPA-TPA 150K-FI		150	32	110	Ball bearing	185	90 x 66	75x45/61x51	8,5	40



**Variants / Accessories**



	Antistatic version, non-marking grey	With synthetic thread guard	With pressed steel thread guard, zinc-plated	With electrostatic powder coating
Technical description page	30	30 + 79	79	
Ref. No. extension	-ELS	Standard	-FA	
Available for wheel Ø [mm]	80 - 125	80 - 125 ball bearing versions	150	Upon request