

Series: LRA-VPA, BRA-VPA

Light duty swivel and fixed castors with bolt hole fitting

40 - 70 kg



Brackets: LRA/BRA Series - Pressed steel, swivel bracket with double ball bearing in the swivel head, bolted wheel axle, zinc-plated.
Detailed description: Page 59 and 76.

Wheels: VPA Series - Tyres: Solid rubber, colour grey, non-marking, 80° shore A.
Rims: Plain bearing version made of high-quality nylon. Ball bearing version made of polypropylene. Shock and impact-resistant, corrosion-resistant, colour black.
Detailed description: Page 92 and 30.

3

Further information on the internet: www.blickle.de

Swivel castors		Fixed castors		Swivel castors with "stop-fix" brake		Wheel Ø	Tyre width	Load capacity	Bearing version	Total height	Plate Ø	Bolt hole Ø	Offset swivel castor
Ref. No.	Ref. No.	Ref. No.	Ref. No.	Ref. No.	Ref. No.	[mm]	[mm]	[kg]		[mm]	[mm]	[mm]	[mm]
LRA-VPA 50G	BRA-VPA 50G	LRA-VPA 50G-FI	LRA-VPA 50K	LRA-VPA 50K-FI	LRA-VPA 50K	50	18	40	Plain bearing	69	43	11	25
LRA-VPA 50K	BRA-VPA 50K	LRA-VPA 50K-FI	LRA-VPA 50K	LRA-VPA 50K-FI	LRA-VPA 50K	50	18	40	Ball bearing	69	43	11	25
LRA-VPA 75G	BRA-VPA 75G	LRA-VPA 75G-FI	LRA-VPA 75K	LRA-VPA 75K-FI	LRA-VPA 75K	75	25	60	Plain bearing	98	43	11	28
LRA-VPA 75K	BRA-VPA 75K	LRA-VPA 75K-FI	LRA-VPA 75K	LRA-VPA 75K-FI	LRA-VPA 75K	75	25	60	Ball bearing	98	43	11	28
LRA-VPA 100G		LRA-VPA 100G-FI	LRA-VPA 100K	LRA-VPA 100K-FI	LRA-VPA 100K	100	25	70	Plain bearing	121	43	11	33
LRA-VPA 100K		LRA-VPA 100K-FI	LRA-VPA 100K	LRA-VPA 100K-FI	LRA-VPA 100K	100	25	70	Ball bearing	121	43	11	33

Variants / Accessories



	Antistatic version, black tyre	With pressed steel thread guard, zinc-plated	With threaded pin M10 x 30	With plug-in pin 11 x 30.5	Synthetic castor sockets for round tubes	With metal expander fitting
Technical description page	30	79	74	75	75	75
Ref. No. extension	-EL	-FA	-GS10	-ES	See below	See below
Available for wheel Ø [mm]	All ball bearing versions	All except ...50K	All swivel castors	All swivel castors	All swivel castors with plug-in pin	All swivel castors

Metal expander fitting

Synthetic castor socket

Internal tube dim. round tube [mm]	Internal tube dim. square tube [mm]	Ref. No. extension	Ref. No.	Internal tube dim. round tube [mm]	Flange dimension Ø x height [mm]	Total length castor socket [mm]
17 - 19	17 - 19	-E01	RHR 20-18/11A	Ø 18,0	Ø 20,0 x 5,0	42
20 - 25	18 - 21	-E02	RHR 22-19/11A	Ø 19,0	Ø 22,0 x 5,0	42
25 - 30	21 - 25	-E03	Further dimensions upon request			
30 - 35	25 - 29	-E04				
35 - 40	29 - 32	-E05				
39 - 45	32 - 38,5	-E07				