

Series: LMDA-VPA

Light duty twin wheel swivel castors with bolt hole fitting


 70 - 100 kg



Brackets: LMDA Series - Pressed steel, with double ball bearing in the swivel head, bolted wheel axle, zinc-plated.
Detailed description: Page 59 and 76.

Wheels: VPA Series - Tyres: Solid rubber, colour grey, non-marking, 80° shore A.
Rims: Plain bearing version made of high-quality nylon. Ball bearing version made of polypropylene. Shock and impact-resistant, corrosion-resistant, colour black.
Detailed description: Page 92 and 30.

Swivel castors		Swivel castors with "stop-fix" brake								
Ref. No.	Ref. No.	Wheel Ø [mm]	Tyre width [mm]	Load capacity [kg]	Bearing version	Total height [mm]	Plate Ø [mm]	Bolt hole Ø [mm]	Offset [mm]	
LMDA-VPA 50G	LMDA-VPA 50G-FI	50	2 x 18	70	Plain bearing	71	41	10,2	31	
LMDA-VPA 50K	LMDA-VPA 50K-FI	50	2 x 18	70	Ball bearing	71	41	10,2	31	
LMDA-VPA 75G	LMDA-VPA 75G-FI	75	2 x 25	100	Plain bearing	98	55	10,2	34	
LMDA-VPA 75K	LMDA-VPA 75K-FI	75	2 x 25	100	Ball bearing	98	55	10,2	34	



Variants / Accessories



	Antistatic version, black tyre
Technical description page	30
Ref. No. extension	-EL
Available for wheel Ø [mm]	All ball bearing versions