

Series: LPA-VPA, BPA-VPA

Light duty swivel and fixed castors

 40 - 70 kg



3


Further information on the internet: www.blickle.de



Brackets: LPA/BPA Series - Pressed steel, swivel bracket with double ball bearing in the swivel head, bolted wheel axle, zinc-plated.
Top plate drawings: Page 70.
Detailed description: Page 59 and 76.

Wheels: VPA Series - Tyres: Solid rubber, colour grey, non-marking, 80° shore A.
Rims: Plain bearing version made of high-quality nylon. Ball bearing version made of polypropylene. Shock and impact-resistant, corrosion-resistant, colour black.
Detailed description: Page 92 and 30.

Swivel castors	Fixed castors	Swivel castors with "stop-fix" brake	Wheel Ø [mm]	Tyre width [mm]	Load capacity [kg]	Bearing version	Total height [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
LPA-VPA 50G	BPA-VPA 50G	LPA-VPA 50G-FI	50	18	40	Plain bearing	71	60 x 60	38x38/48x48	6,2	25
LPA-VPA 50K	BPA-VPA 50K	LPA-VPA 50K-FI	50	18	40	Ball bearing	71	60 x 60	38x38/48x48	6,2	25
LPA-VPA 75G	BPA-VPA 75G	LPA-VPA 75G-FI	75	25	60	Plain bearing	100	60 x 60	38x38/48x48	6,2	28
LPA-VPA 75K	BPA-VPA 75K	LPA-VPA 75K-FI	75	25	60	Ball bearing	100	60 x 60	38x38/48x48	6,2	28
LPA-VPA 100G		LPA-VPA 100G-FI	100	25	70	Plain bearing	123	60 x 60	38x38/48x48	6,2	33
LPA-VPA 100K		LPA-VPA 100K-FI	100	25	70	Ball bearing	123	60 x 60	38x38/48x48	6,2	33



Variants / Accessories



	Antistatic version, black tyre	With pressed steel thread guard, zinc-plated
Technical description page	30	79
Ref. No. extension	-EL	-FA
Available for wheel Ø [mm]	All ball bearing versions	All except ...50K