

Series: LKU-TPA
Synthetic swivel castors

100 - 130 kg



Brackets: LKU Series - Made of glass-fibre reinforced synthetic with double-sealed grooved ball bearing in the swivel head, internal thread M12 in the bolt hole. Elegant, shapely design. Colour light grey. Detailed description: Page 61.

Wheels: TPA Series - Treads: Made of thermoplastic rubber, colour grey, non-marking, 85° shore A. Wheel centres: Made of polypropylene, colour light grey, ball bearing and thread guard. Detailed description: Page 84 and 30.

4

Further information on the Internet: www.blickle.de

Swivel castors		Swivel castors with "stop-fix" brake		Wheel Ø	Wheel width	Load capacity	Bearing version	Total height	Bolt hole Ø	Offset
Ref. No.	Ref. No.	[mm]	[mm]	[kg]				[mm]	[mm]	[mm]
LKU-TPA 101K	LKU-TPA 101K-FI	100	32	100	Ball bearing	145	M12	38		
LKU-TPA 126K	LKU-TPA 126K-FI	125	32	110	Ball bearing	165	M12	47		
LKU-TPA 150K	LKU-TPA 150K-FI	150	32	130	Ball bearing	195	M12	49		
LKU-TPA 200K	LKU-TPA 200K-FI	200	32	130	Ball bearing	251	M12	67		

Variants / Accessories



	With directional lock, combined with wheel brake	Bolt hole with M12 bolt, protruding 25 mm	With threaded pin M10 x 20 or M12 x 20	With aluminium expander fitting	With synthetic expander fitting	Steel plug-in stem	With plate fitting
Technical description page	61	61	74	75	75	74	70
Ref. No. extension	-RI-FI	-SC1225	-GS10 / -GS12	See below	See below	See below	See below
Available for wheel Ø [mm]	125	All sizes	All sizes	All sizes	All sizes	All sizes	All sizes

Aluminium expander fitting		Synthetic expander fitting		With steel plug-in stem		Plate fitting (total height + 10 mm)		
Internal tube diameter [mm]	Ref. No. extension	Internal tube dim. round tube [mm]	Ref. No. extension	Dimensions [mm]	Ref. No. extension	Dimensions [mm]	Ref. No. extension	
Ø 17 - 19	-EA1	Ø 19 - 20	-EK2	Ø 18,0 x 62	-ZA51	Plate dimensions	78 x 68	-P51
Ø 19 - 21	-EA2	Ø 20 - 22	-EK3	Ø 19,0 x 45	-ZA52	Hole spacing	61 x 51 / 50 x 42	
Ø 21 - 24	-EA3	Ø 22 - 24	-EK4	Ø 20,5 x 45	-ZA53	Hole-Ø	8,5	
Ø 24 - 29	-EA4	Ø 25 - 27	-EK5	Ø 21,5 x 45	-ZA54	Plate dimensions	80 x 80	-P52
Ø 29 - 32	-EA5			Ø 22,0 x 45	-ZA55	Hole spacing	60 x 60 / 50 x 60	
□ 21	-EAQ			Ø 25,5 x 45	-ZA57	Hole-Ø	8,5	-P53
				Ø 27,5 x 45	-ZA58	Plate dimensions	90 x 70	
						Hole spacing	75 x 45 / 70 x 50	
						Hole-Ø	8,5	