Blickle®
Castors+Wheels

Series: LKUE-TPA, LKUE-PTH

Synthetic swivel castors, antistatic

100 - 130 kg

Brackets: LKUE Series - Made of glass-fibre reinforced synthetic with double-sealed grooved ball bearing in the swivel head, internal thread M12 in the bolt hole. Elegant, shapely design, antistatic. Colour light grey.
Detailed description: Page 61.

Wheels: Treads: TPA series: Made of thermoplastic rubber, antistatic, colour grey, non-marking, 85° shore A, vulcanised, non-detachable connection. PTH series: Made of injection-moulded polyurethane, antistatic, colour grey, non-marking, 98° shore A, abrasion-resistant, non-staining, low rolling resistance. Wheel centres: TPA series: Made of polypropylene, antistatic, colour black, ball bearing and synthetic thread guard. PTH series: Made of high-quality nylon, antistatic, colour grey, shock and impact-resistant, corrosion-resistant, ball bearing.
Detailed description: Page 30 and 32.

Swivel castors	Swivel castors with "stop-fix" brake							
Ref. No.	Ref. No.	Wheel Ø [mm]	Wheel width [mm]	Load capacity [kg]	Bearing version	Total height [mm]	Bolt hole Ø [mm]	Offset [mm]
LKUE-TPA 101K-ELS	LKUE-TPA 101K-ELS-FI	100	32	100	Ball bearing	145	M12	38
LKUE-TPA 126K-ELS	LKUE-TPA 126K-ELS-FI	125	32	110	Ball bearing	165	M12	47
LKUE-PTH 150K-ELS	LKUE-PTH 150K-ELS-FI	150	32	130	Ball bearing	195	M12	49
LKUE-PTH 200K-ELS	LKUE-PTH 200K-ELS-FI	200	32	130	Ball bearing	251	M12	67

Variants / Accessories

	With directional lock, combined with wheel brake	Bolt hole with M12 bolt, protruding 25 mm	With threaded pin M10 x 20 or. M12 x 20	With aluminium expander fitting	Steel plug-in stem	With plate fitting
Technical description page	61	61	74	75	74	70
Ref. No. extension	-RI-FI	-SC1225	-GS10 / -GS12	see below	see below	see below
Available for wheel Ø [mm]	Upon request	All sizes	All sizes	All sizes	All sizes	All sizes

Aluminium expander fitting

Internal tube diameter [mm]	Ref. No. extension
Ø 17 - 19	-EA1
Ø 19 - 21	-EA2
Ø 21 - 24	-EA3
Ø 24 - 29	-EA4
Ø 29 - 32	-EA5
□ 21	-EAQ

With steel plug-in stem

Dimensions [mm]	Ref. No. extension
Ø 18,0 x 62	-ZA51
Ø 19,0 x 45	-ZA52
Ø 20,5 x 45	-ZA53
Ø 21,5 x 45	-ZA54
Ø 22,0 x 45	-ZA55
Ø 25,5 x 45	-ZA57
Ø 27,5 x 45	-ZA58

Plate fitting (total height + 10 mm)

	Dimensions [mm]	Ref. No. extension
Plate dimensions Hole spacing Hole-Ø	78 x 68 61 x 51 / 50 x 42 8,5	-P51
Plate dimensions Hole spacing Hole-Ø	80 x 80 60 x 60 / 50 x 60 8,5	-P52
Plate dimensions Hole spacing Hole-Ø	90 x 70 75 x 45 / 70 x 50 8,5	-P53