

Series: L-V, B-V, BH-V

Pressed steel swivel and fixed castors, medium duty brackets

50 - 385 kg



5



Brackets: L/B/BH Series - Pressed steel, swivel bracket with double ball bearing in the reinforced swivel head, dynamically pressed in accordance with special Blickle procedure resulting in an extremely low swivel head play and a long service life, strong central kingpin (wheel Ø 160-280 mm) and swivel head sealing (except for brackets with 175x175 mm plate), bolted wheel axle, zinc-plated.

Wheels: V Series - Tyres: Standard solid rubber, colour black, 80° shore A.
Rims: Pressed steel, tubular steel hub, roller or ball bearing, zinc-plated.

This special Blickle rim design is extremely strong, even under extreme shock and impact loads. Smooth and elegant design ("Die gute Industrieform" design award).


Top plate drawings: Page 71.
Detailed description: Page 62 and 76.

Detailed description: Page 130, 131 and 33.

Further information on the internet: www.blickle.de

Swivel castors	Fixed castors	Swivel castors with "stop-fix" brake	Wheel Ø [mm]	Tyre width [mm]	Load capacity [kg]	Bearing version	Total height [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
Ref. No.	Ref. No.	Ref. No.									
L-V 80R	B-V 80R	L-V 80R-FI	80	25	50	Roller bearing	102	100 x 85	80 x 60	9	38
L-V 100R	B-V 100R	L-V 100R-FI	100	30	70	Roller bearing	125	100 x 85	80 x 60	9	36
L-V 125R	B-V 125R	L-V 125R-FI	125	37,5	100	Roller bearing	150	100 x 85	80 x 60	9	40
L-V 140R	B-V 140R	L-V 140R-FI	140	37,5	115	Roller bearing	170	140 x 110	105 x 75-80	11	50
L-V 162R	B-V 162R	L-V 162R-FI	160	40	135	Roller bearing	195	140 x 110	105 x 75-80	11	60
L-V 182R	B-V 182R	L-V 182R-FI	180	50	170	Roller bearing	215	140 x 110	105 x 75-80	11	60
L-V 202R	B-V 202R	L-V 202R-FI	200	50	205	Roller bearing	235	140 x 110	105 x 75-80	11	65
L-V 200K	B-V 200K	L-V 200K-FI	200	50	205	Ball bearing	235	140 x 110	105 x 75-80	11	65
L-V 205R	B-V 205R	*	200	65	225	Roller bearing	240	140 x 110	105 x 75-80	11	70
L-V 252R-3	BH-V 252R	*	250	60	295	Roller bearing	295	140 x 110	105 x 75-80	11	77
L-V 252R	B-V 252R	*	250	60	295	Roller bearing	295	175 x 175	140 x 140	15	70
L-V 256K	B-V 256K	*	250	85	350	Ball bearing	295	220 x 120	190 x 75	15	70
L-V 282R	B-V 282R	*	280	70	385	Roller bearing	318	175 x 175	140 x 140	15	78
			280	70	385	Roller bearing	318	220 x 120	190 x 75	15	

* For the "stop-top" brake version, refer to Variants / Accessories.



Variants / Accessories



	With non-marking grey tyre	With pressed steel thread guard, zinc-plated	With "stop-top" brake	With directional lock (retro fit)** 1 x 360°
Technical description page	33	79	77	78
Ref. No. extension	-SG	-FA	-ST	RI-05.03
Available for wheel Ø [mm]	80 - 200x50, 250x60	80 - 200	All sizes	160-200x50

** Only for swivel castors without brake.