

Series: LE-VPP, BE-VPP, B-VPP

**Pressed steel swivel and fixed castors**

50 - 205 kg



**Brackets:** LE/BE/B Series - Pressed steel, swivel bracket with double ball bearing in the swivel head, dynamically pressed in accordance with special Blickle procedure resulting in an extremely low swivel head play and a long service life, with swivel head sealing, bolted wheel axle, zinc-plated.

Top plate drawings: Page 71.  
Detailed description: Page 62 and 76.

**Wheels:** VPP Series - Tyres: Standard solid rubber, colour black, 80° shore A or 90° shore A with wheel dimensions of 80x32 mm.  
Rims: Made of polypropylene, shock and impact-resistant, corrosion-resistant, plain or roller bearing, colour black.  
Detailed description: Page 133, 134 and 34.

Swivel castors	Fixed castors	Swivel castors with "stop-fix" brake	Wheel Ø [mm]	Tyre width [mm]	Load capacity [kg]	Bearing version	Total height [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
Ref. No.	Ref. No.	Ref. No.									
LE-VPP 80G	B-VPP 80G	LE-VPP 80G-FI	80	25	50	Plain bearing	102	100 x 85	80 x 60	9	38
LE-VPP 80R	B-VPP 80R	LE-VPP 80R-FI	80	25	50	Roller bearing	102	100 x 85	80 x 60	9	38
LE-VPP 82G	B-VPP 82G	LE-VPP 82G-FI	80	32	100	Plain bearing	102	100 x 85	80 x 60	9	38
LE-VPP 100G	BE-VPP 100G	LE-VPP 100G-FI	100	30	70	Plain bearing	125	100 x 85	80 x 60	9	36
LE-VPP 100R	BE-VPP 100R	LE-VPP 100R-FI	100	30	70	Roller bearing	125	100 x 85	80 x 60	9	36
LE-VPP 125G	BE-VPP 125G	LE-VPP 125G-FI	125	37,5	100	Plain bearing	150	100 x 85	80 x 60	9	40
LE-VPP 125R	BE-VPP 125R	LE-VPP 125R-FI	125	37,5	100	Roller bearing	150	100 x 85	80 x 60	9	40
LE-VPP 150G	B-VPP 150G	LE-VPP 150G-FI	150	40	135	Plain bearing	190	140 x 110	105 x 75-80	11	54
LE-VPP 150R	B-VPP 150R	LE-VPP 150R-FI	150	40	135	Roller bearing	190	140 x 110	105 x 75-80	11	54
LE-VPP 160G	B-VPP 160G	LE-VPP 160G-FI	160	40	135	Plain bearing	195	140 x 110	105 x 75-80	11	54
LE-VPP 160R	B-VPP 160R	LE-VPP 160R-FI	160	40	135	Roller bearing	195	140 x 110	105 x 75-80	11	54
LE-VPP 180G	B-VPP 180G	LE-VPP 180G-FI	180	50	170	Plain bearing	215	140 x 110	105 x 75-80	11	54
LE-VPP 180R	B-VPP 180R	LE-VPP 180R-FI	180	50	170	Roller bearing	215	140 x 110	105 x 75-80	11	54
LE-VPP 200G	B-VPP 200G	LE-VPP 200G-FI	200	50	205	Plain bearing	235	140 x 110	105 x 75-80	11	54
LE-VPP 200R	B-VPP 200R	LE-VPP 200R-FI	200	50	205	Roller bearing	235	140 x 110	105 x 75-80	11	54



**Variants / Accessories**



	With non-marking grey tyre	With pressed steel thread guard, zinc-plated	With "stop-top" brake	With directional lock (retro fit)* 1 x 360°
Technical description page	34	79	77	78
Ref. No. extension	-SG	-FA	-ST	RI-03.03
Available for wheel Ø [mm]	All sizes	All sizes	150 - 200	150 - 200

\* Only for swivel castors without brake.