

Series: LER-VPP

**Pressed steel swivel castors with bolt hole fitting**

 50 - 205 kg



**Brackets:** LER Series - Pressed steel, with bolt hole, double ball bearing in the swivel head and strong central kingpin, dynamically pressed in accordance with special Blickle procedure resulting in an extremely low swivel head play and a long service life, bolted wheel axle, zinc-plated.  
Detailed description: Page 62 and 76.

**Wheels:** VPP Series - Tyres: Standard solid rubber, colour black, 80° shore A or 90° shore A with wheel dimensions 80x32 mm.  
Rims: Made of polypropylene, shock and impact-resistant, corrosion-resistant, plain bearing, colour black.  
Detailed description: Page 133, 134 and 34.

5

Further information on the internet: [www.blickle.de](http://www.blickle.de)

Swivel castors		Swivel castors with "stop-fix" brake		Wheel Ø	Tyre width	Load capacity	Bearing version	Total height	Plate Ø	Bolt hole Ø	Offset
Ref. No.	Ref. No.	[mm]	[mm]	[kg]				[mm]	[mm]	[mm]	[mm]
LER-VPP 80G	LER-VPP 80G-FI	80	25	50	Plain bearing	102	70	13	38		
LER-VPP 82G	LER-VPP 82G-FI	80	32	100	Plain bearing	102	70	13	38		
LER-VPP 100G	LER-VPP 100G-FI	100	30	70	Plain bearing	125	70	13	36		
LER-VPP 125G	LER-VPP 125G-FI	125	37,5	100	Plain bearing	150	70	13	40		
LER-VPP 150G	LER-VPP 150G-FI	150	40	135	Plain bearing	190	88	13	54		
LER-VPP 160G	LER-VPP 160G-FI	160	40	135	Plain bearing	195	88	13	54		
LER-VPP 180G	LER-VPP 180G-FI	180	50	170	Plain bearing	215	88	13	54		
LER-VPP 200G	LER-VPP 200G-FI	200	50	205	Plain bearing	235	88	13	54		



**Variants / Accessories**



	With non-marking grey tyre	With pressed steel thread guard, zinc-plated
Technical description page	34	79
Ref. No. extension	-SG	-FA
Available for wheel Ø [mm]	All sizes	All sizes