

Series: LEZ-VPP

Pressed steel swivel castors with stem fitting

 50 - 205 kg



Brackets: LEZ Series - Pressed steel, with steel stems, with double ball bearing in the swivel head, dynamically pressed in accordance with special Blickle procedure resulting in an extremely low swivel head play and a long service life, bolted wheel axle, zinc-plated.
Detailed description: Page 62 and 76.

Wheels: VPP Series - Tyres: Standard solid rubber, colour black, 80° shore A or 90° shore A with wheel dimensions 80x32 mm.
Rims: Made of polypropylene, shock and impact-resistant, corrosion-resistant, plain bearing, colour black.
Detailed description: Page 133, 134 and 34.

51

Swivel castors		Swivel castors with "stop-fix" brake		Wheel Ø [mm]	Tyre width [mm]	Load capacity [kg]	Bearing version	Total height [mm]	Stem Ø [mm]	Stem length [mm]	Offset [mm]
Ref. No.	Ref. No.	Ref. No.	Ref. No.								
LEZ-VPP 80G	LEZ-VPP 80G-FI	LEZ-VPP 80G	LEZ-VPP 80G-FI	80	25	50	Plain bearing	102	20	50	38
LEZ-VPP 82G	LEZ-VPP 82G-FI	LEZ-VPP 82G	LEZ-VPP 82G-FI	80	32	100	Plain bearing	102	20	50	38
LEZ-VPP 100G	LEZ-VPP 100G-FI	LEZ-VPP 100G	LEZ-VPP 100G-FI	100	30	70	Plain bearing	125	20	50	36
LEZ-VPP 125G	LEZ-VPP 125G-FI	LEZ-VPP 125G	LEZ-VPP 125G-FI	125	37,5	100	Plain bearing	150	20	50	40
LEZ-VPP 150G-22	LEZ-VPP 150G-22-FI	LEZ-VPP 150G-22	LEZ-VPP 150G-22-FI	150	40	135	Plain bearing	190	22	60	54
LEZ-VPP 150G-27	LEZ-VPP 150G-27-FI	LEZ-VPP 150G-27	LEZ-VPP 150G-27-FI	150	40	135	Plain bearing	190	27	60	54
LEZ-VPP 160G-22	LEZ-VPP 160G-22-FI	LEZ-VPP 160G-22	LEZ-VPP 160G-22-FI	160	40	135	Plain bearing	195	22	60	54
LEZ-VPP 160G-27	LEZ-VPP 160G-27-FI	LEZ-VPP 160G-27	LEZ-VPP 160G-27-FI	160	40	135	Plain bearing	195	27	60	54
LEZ-VPP 180G-22	LEZ-VPP 180G-22-FI	LEZ-VPP 180G-22	LEZ-VPP 180G-22-FI	180	50	170	Plain bearing	215	22	60	54
LEZ-VPP 180G-27	LEZ-VPP 180G-27-FI	LEZ-VPP 180G-27	LEZ-VPP 180G-27-FI	180	50	170	Plain bearing	215	27	60	54
LEZ-VPP 200G-22	LEZ-VPP 200G-22-FI	LEZ-VPP 200G-22	LEZ-VPP 200G-22-FI	200	50	205	Plain bearing	235	22	60	54
LEZ-VPP 200G-27	LEZ-VPP 200G-27-FI	LEZ-VPP 200G-27	LEZ-VPP 200G-27-FI	200	50	205	Plain bearing	235	27	60	54

Further information on the internet: www.blickle.de

Variants / Accessories



	With non-marking grey tyre	With pressed steel thread guard, zinc-plated
Technical description page	34	79
Ref. No. extension	-SG	-FA
Available for wheel Ø [mm]	All sizes	All sizes