

Series: L-VPP, B-VPP, BH-VPP

**Pressed steel swivel and fixed castors, medium duty brackets**

50 - 295 kg



**Brackets:** L/B/BH Series - Pressed steel, swivel bracket with double ball bearing in the reinforced swivel head, dynamically pressed in accordance with special Blickle procedure resulting in an extremely low swivel head play and a long service life, strong central kingpin (wheel Ø 160-250 mm) and swivel head sealing (except for brackets with 175x175 mm plate), bolted wheel axle, zinc-plated.  
Top plate drawings: Page 71.  
Detailed description: Page 62 and 76.

**Wheels:** VPP Series - Tyres: Standard solid rubber, colour black, 80° shore A or 90° shore A with wheel dimensions of 80x32 mm.  
Rims: Made of polypropylene, shock and impact-resistant, corrosion-resistant, plain, roller or ball bearing, colour black.  
Detailed description: Page 133, 134 and 34.

5

Further information on the internet: [www.blickle.de](http://www.blickle.de)

Swivel castors	Fixed castors	Swivel castors with "stop-fix" brake	Wheel Ø [mm]	Tyre width [mm]	Load capacity [kg]	Bearing version	Total height [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
L-VPP 80G	B-VPP 80G	L-VPP 80G-FI	80	25	50	Plain bearing	102	100 x 85	80 x 60	9	38
L-VPP 80R	B-VPP 80R	L-VPP 80R-FI	80	25	50	Roller bearing	102	100 x 85	80 x 60	9	38
L-VPP 82G	B-VPP 82G	L-VPP 82G-FI	80	32	100	Plain bearing	102	100 x 85	80 x 60	9	38
L-VPP 100G	B-VPP 100G	L-VPP 100G-FI	100	30	70	Plain bearing	125	100 x 85	80 x 60	9	36
L-VPP 100R	B-VPP 100R	L-VPP 100R-FI	100	30	70	Roller bearing	125	100 x 85	80 x 60	9	36
L-VPP 125G	B-VPP 125G	L-VPP 125G-FI	125	37,5	100	Plain bearing	150	100 x 85	80 x 60	9	40
L-VPP 125R	B-VPP 125R	L-VPP 125R-FI	125	37,5	100	Roller bearing	150	100 x 85	80 x 60	9	40
L-VPP 140G	B-VPP 140G	L-VPP 140G-FI	140	37,5	115	Plain bearing	170	140 x 110	105 x 75-80	11	50
L-VPP 140R	B-VPP 140R	L-VPP 140R-FI	140	37,5	115	Roller bearing	170	140 x 110	105 x 75-80	11	50
L-VPP 160G	B-VPP 160G	L-VPP 160G-FI	160	40	135	Plain bearing	195	140 x 110	105 x 75-80	11	60
L-VPP 160R	B-VPP 160R	L-VPP 160R-FI	160	40	135	Roller bearing	195	140 x 110	105 x 75-80	11	60
L-VPP 180G	B-VPP 180G	L-VPP 180G-FI	180	50	170	Plain bearing	215	140 x 110	105 x 75-80	11	60
L-VPP 180R	B-VPP 180R	L-VPP 180R-FI	180	50	170	Roller bearing	215	140 x 110	105 x 75-80	11	60
L-VPP 200G	B-VPP 200G	L-VPP 200G-FI	200	50	205	Plain bearing	235	140 x 110	105 x 75-80	11	65
L-VPP 200R	B-VPP 200R	L-VPP 200R-FI	200	50	205	Roller bearing	235	140 x 110	105 x 75-80	11	65
L-VPP 200K	B-VPP 200K	L-VPP 200K-FI	200	50	205	Ball bearing	235	140 x 110	105 x 75-80	11	65
L-VPP 250G-3	BH-VPP 250G	*	250	60	295	Plain bearing	295	140 x 110	105 x 75-80	11	77
L-VPP 250R-3	BH-VPP 250R	*	250	60	295	Roller bearing	295	140 x 110	105 x 75-80	11	77
L-VPP 256G	B-VPP 256G	*	250	85	250	Plain bearing	295	175 x 175	140 x 140	15	70
			250	85	250	Plain bearing	295	220 x 120	190 x 75	15	

\* For the "stop-top" brake version, refer to Variants / Accessories.



**Variants / Accessories**

	With non-marking grey tyre	With pressed steel thread guard, zinc-plated	With "stop-top" brake	With directional lock (retro fit)** 1 x 360°
Technical description page	34	79	77	78
Ref. No. extension	-SG	-FA	-ST	RI-05.03
Available for wheel Ø [mm]	80 - 250x60	80 - 200	All sizes	160 - 200

\*\* Only for swivel castors without brake.