

Series: LER-TPA, LER-TPP

Pressed steel swivel castors with bolt hole fitting

 90 - 220 kg



Brackets: LER Series - Pressed steel, with bolt hole, double ball bearing in the swivel head and strong central kingpin, dynamically pressed in accordance with special Blickle procedure resulting in an extremely low swivel head play and a long service life, bolted wheel axle, zinc-plated.
Detailed description: Page 62 and 76.

Wheels: TPA/TPP Series - Treads: Made of thermoplastic rubber, colour grey, non-marking, 85° shore A. Wheel centres: Made of polypropylene, colour light grey, colour black for “-ELS” version (refer to Variants / Accessories), plain or ball bearing. As standard, ball bearing versions are supplied with bearing sealing.
Detailed description: Page 140, 30 and 34.

5

Further information on the internet: www.blickle.de

Swivel castors		Swivel castors with “stop-fix” brake		Wheel Ø	Wheel width	Load capacity	Bearing version	Total height	Plate Ø	Bolt hole Ø	Offset
Ref. No.	Ref. No.	(D) [mm]	[mm]	[kg]	[mm]	[mm]		[mm]	[mm]	[mm]	[mm]
LER-TPA 80G	LER-TPA 80G-FI	80	32	90	32	102	Plain bearing	70	13	38	
LER-TPA 102G	LER-TPA 102G-FI	100	32	100	32	125	Plain bearing	70	13	36	
LER-TPA 127G	LER-TPA 127G-FI	125	32	110	32	150	Plain bearing	70	13	40	
LER-TPP 160KD	LER-TPP 160KD-FI	160	40	180	40	195	Ball bearing	88	13	54	
LER-TPP 200KD	LER-TPP 200KD-FI	200	40	220	40	235	Ball bearing	88	13	54	



Variants / Accessories



Antistatic version, non-marking grey

Technical description page	30
Ref. No. extension	-ELS
Available for wheel Ø [mm]	80 - 125