

Series: L-VW, B-VW, BH-VW

Pressed steel swivel and fixed castors, medium duty brackets

50 - 200 kg



Brackets: L/BH Series - Pressed steel, swivel bracket with double ball bearing in the reinforced swivel head, dynamically pressed in accordance with special Blickle procedure resulting in an extremely low swivel head play and a long service life, strong central kingpin (wheel Ø 160-260 mm) and swivel head sealing (except for brackets with 175x175 mm plate), bolted wheel axle, zinc-plated.

Wheels: VW Series - Tyres: Blickle®-Soft soft rubber, round profile, colour black, 50° shore A, **noise-absorbing**.

Rims: Pressed steel, tubular steel hub, roller or ball bearing, zinc-plated.

This special Blickle rim design is extremely strong, even under extreme shock and impact loads. Smooth and elegant design ("Die gute Industrieform" design award).


Top plate drawings: Page 71.
Detailed description: Page 62 and 76.

Detailed description: Page 146 and 35.

Swivel castors	Fixed castors	Swivel castors with "stop-fix" brake
----------------	---------------	--------------------------------------

Ref. No.	Ref. No.	Ref. No.	Wheel Ø [mm]	Tyre width [mm]	Load capacity [kg]	Bearing version	Total height [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
L-VW 125R	B-VW 125R	L-VW 125R-FI	125	37,5	50	Roller bearing	150	100 x 85	80 x 60	9	40
L-VW 162R	B-VW 162R	L-VW 162R-FI	160	40	70	Roller bearing	195	140 x 110	105 x 75-80	11	60
L-VW 202R	B-VW 202R	L-VW 202R-FI	200	50	100	Roller bearing	235	140 x 110	105 x 75-80	11	65
L-VW 252R-3	BH-VW 252R	*	250	60	160	Roller bearing	295	140 x 110	105 x 75-80	11	77
L-VW 260R	B-VW 260R	*	260	85	200	Roller bearing	308	175 x 175	140 x 140	15	78
L-VW 280K	B-VW 280K	*	260	85	200	Roller bearing	308	220 x 120	190 x 75	15	
			260	85	200	Ball bearing	308	175 x 175	140 x 140	15	78
			260	85	200	Ball bearing	308	220 x 120	190 x 75	15	

* For the "stop-top" brake version, refer to Variants / Accessories.



Variants / Accessories



	With non-marking grey tyre	With pressed steel thread guard, zinc-plated	With "stop-top" brake	With directional lock (retro fit)** 1 x 360°
Technical description page	35	79	77	78
Ref. No. extension	-SG	-FA	-ST	RI-05.03
Available for wheel Ø [mm]	Upon request	125 - 200	All sizes	160 + 200

** Only for swivel castors without brake.

Further information on the internet: www.blickle.de