

Series: L-VWPP, B-VWPP, BH-VWPP
**Pressed steel swivel and fixed castors,
medium duty brackets**

50 - 200 kg




Brackets: L/BH Series - Pressed steel, swivel bracket with double ball bearing in the reinforced swivel head, dynamically pressed in accordance with special Blickle procedure resulting in an extremely low swivel head play and a long service life, strong central kingpin (wheel Ø 160-260 mm) and swivel head sealing (except for brackets with 175x175 mm plate), bolted wheel axle, zinc-plated.

Wheels: VWPP Series - Tyres: Blickle®-Soft soft rubber, round profile, colour black, 50° shore A, **noise-absorbing**. Rims: Made of polypropylene, shock and impact-resistant, corrosion-resistant, plain or ball bearing, colour black.
Detailed description: Page 148 and 35.

Top plate drawings: Page 71.
Detailed description: Page 62 and 76.

Swivel castors	Fixed castors	Swivel castors with "stop-fix" brake	Wheel Ø [mm]	Tyre width [mm]	Load capacity [kg]	Bearing version	Total height [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
Ref. No.	Ref. No.	Ref. No.									
L-VWPP 125G	B-VWPP 125G	L-VWPP 125G-FI	125	37,5	50	Plain bearing	150	100 x 85	80 x 60	9	40
L-VWPP 160G	B-VWPP 160G	L-VWPP 160G-FI	160	40	70	Plain bearing	195	140 x 110	105 x 75-80	11	60
L-VWPP 200G	B-VWPP 200G	L-VWPP 200G-FI	200	50	100	Plain bearing	235	140 x 110	105 x 75-80	11	65
L-VWPP 250G-3	BH-VWPP 250G	*	250	60	160	Plain bearing	295	140 x 110	105 x 75-80	11	77
L-VWPP 260G	B-VWPP 260G	*	260	85	200	Plain bearing	308	175 x 175	140 x 140	15	78
L-VWPP 280K	B-VWPP 280K	*	260	85	200	Plain bearing	308	220 x 120	190 x 75	15	
			260	85	200	Ball bearing	308	175 x 175	140 x 140	15	78
			260	85	200	Ball bearing	308	220 x 120	190 x 75	15	

* For the "stop-top" brake version, refer to Variants / Accessories.



Variants / Accessories



	With non-marking grey tyre	With pressed steel thread guard, zinc-plated	With "stop-top" brake	With directional lock (retro fit)** 1 x 360°
Technical description page	35	79	77	78
Ref. No. extension	-SG	-FA	-ST	RI-05.03
Available for wheel Ø [mm]	Upon request	125 - 200	All sizes	160 + 200

** Only for swivel castors without brake.

Further information on the internet: www.blickle.de