



Series: RD
**Wheels with semi-elastic solid rubber tyres,
 "Blickle® Comfort",
 pressed steel rim**
 100 - 650 kg



Tyres: Blickle® Comfort solid rubber, two components, hard rubber core, elastic tread, 65° shore A, high operational comfort, colour black.

Rims: Pressed steel, tubular steel hub, roller or ball bearing, zinc-plated.

This special Blickle rim design is extremely strong, even under extreme shock and impact loads. Smooth and elegant design ("Die gute Industrieform" design award).

Detailed description: Page 36.

6

Further information on the internet: www.blickle.de

Wheels

Ref. No.	Wheel Ø (D) [mm]	Tyre width (T2) [mm]	Load capacity [kg]	Bearing version	Axle bore Ø (d) [mm]	Hub length (T1) [mm]
RD 100/15R	100	30	100	Roller bearing	15	45
RD 125/15R	125	37,5	120	Roller bearing	15	45
RD 140/15R	140	37,5	175	Roller bearing	15	45
RD 162/20R	160	40	225	Roller bearing	20	60
RD 182/20R	180	50	300	Roller bearing	20	60
RD 202/20R	200	50	350	Roller bearing	20	60
RD 200/20K	200	50	350	Ball bearing	20	60
RD 252/25R	250	60	450	Roller bearing	25	65
RD 250/25K	250	60	450	Ball bearing	25	65
RD 282/25R	280	70	650	Roller bearing	25	75
RD 280/25K	280	70	650	Ball bearing	25	75

Variants / Accessories



With non-marking grey tyre, 56° shore A

Technical description page	36
Ref. No. extension	-VLI
Available for wheel Ø [mm]	100 - 250

