

Series: L-RD, B-RD, BH-RD

Pressed steel swivel and fixed castors, medium duty brackets

100 - 600 kg



Brackets: L/B/BH Series - Pressed steel, swivel bracket with double ball bearing in the reinforced swivel head, dynamically pressed in accordance with special Blickle procedure resulting in an extremely low swivel head play and a long service life, strong central kingpin (wheel Ø 160-280 mm) and swivel head sealing (except for brackets with 175x175 mm plate), bolted wheel axle, zinc-plated.

Top plate drawings: Page 71.
Detailed description: Page 62 and 76.


Wheels: RD Series - Tyres: Blickle® Comfort solid rubber, two components, hard rubber core, elastic tread, 65° shore A, high operational comfort, colour black. Rims: Pressed steel, tubular steel hub, roller or ball bearing, zinc-plated.

This special Blickle rim design is extremely strong, even under extreme shock and impact loads. Smooth and elegant design ("Die gute Industrieform" design award).

Detailed description: Page 150 and 36.

Swivel castors	Fixed castors	Swivel castors with "stop-fix" brake	Wheel Ø [mm]	Tyre width [mm]	Load capacity [kg]	Bearing version	Total height [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
L-RD 100R	B-RD 100R	L-RD 100R-FI	100	30	100	Roller bearing	125	100 x 85	80 x 60	9	36
L-RD 125R	B-RD 125R	L-RD 125R-FI	125	37,5	120	Roller bearing	150	100 x 85	80 x 60	9	40
L-RD 140R	B-RD 140R	L-RD 140R-FI	140	37,5	175	Roller bearing	170	140 x 110	105 x 75-80	11	50
L-RD 162R	B-RD 162R	L-RD 162R-FI	160	40	225	Roller bearing	195	140 x 110	105 x 75-80	11	60
L-RD 182R	B-RD 182R	L-RD 182R-FI	180	50	300	Roller bearing	215	140 x 110	105 x 75-80	11	60
L-RD 202R	B-RD 202R	L-RD 202R-FI	200	50	350	Roller bearing	235	140 x 110	105 x 75-80	11	65
L-RD 200K	B-RD 200K	L-RD 200K-FI	200	50	350	Ball bearing	235	140 x 110	105 x 75-80	11	65
L-RD 252R-3	BH-RD 252R	*	250	60	450	Roller bearing	295	140 x 110	105 x 75-80	11	77
L-RD 252R	B-RD 252R	*	250	60	450	Roller bearing	295	175 x 175	140 x 140	15	70
L-RD 250K	B-RD 250K	*	250	60	450	Roller bearing	295	220 x 120	190 x 75	15	70
L-RD 282R	B-RD 282R	*	280	70	600	Roller bearing	318	175 x 175	140 x 140	15	78
L-RD 280K	B-RD 280K	*	280	70	600	Roller bearing	318	220 x 120	190 x 75	15	78
			280	70	600	Ball bearing	318	175 x 175	140 x 140	15	78
			280	70	600	Ball bearing	318	220 x 120	190 x 75	15	78

* For the "stop-top" brake version, refer to Variants / Accessories.



Variants / Accessories



	With non-marking grey tyre, 56° shore A	With pressed steel thread guard, zinc-plated	With "stop-top" brake	With directional lock (retro fit)** 1 x 360°
Technical description page	36	79	77	78
Ref. No. extension	-VLI	-FA	-ST	RI-05.03
Available for wheel Ø [mm]	100 - 250	100 - 200	All sizes	160 - 200

** Only for swivel castors without brake.

Further information on the internet: www.blickle.de