

Series: ALEV

Heavy duty wheels with elastic solid rubber tyres, aluminium wheel centre

 180 - 550 kg



Tyres: Elastic solid rubber, smooth rolling quality, colour black, 65° shore A, vulcanised, non-detachable connection, low rolling resistance.
Wheel centres: Made of aluminium die-cast, corrosion-resistant, ball bearing, colour aluminium.
Detailed description: Page 37.

Wheels

Ref. No.	Wheel Ø (D) [mm]	Tyre width (T2) [mm]	Load capacity [kg]	Bearing version	Axle bore Ø (d) [mm]	Hub length (T1) [mm]
ALEV 100/15K	100	40	180	Ball bearing	15	40
ALEV 125/15K	125	40	250	Ball bearing	15	45
ALEV 127/20K	125	50	270	Ball bearing	20	60
ALEV 140/20K	140	40	270	Ball bearing	20	60
ALEV 150/20K	150	54	350	Ball bearing	20	60
ALEV 150/25K	150	54	350	Ball bearing	25	60
ALEV 161/15K	160	40	300	Ball bearing	15	60
ALEV 160/20K	160	50	350	Ball bearing	20	60
ALEV 160/25K	160	50	350	Ball bearing	25	60
ALEV 180/20K	180	50	400	Ball bearing	20	60
ALEV 180/25K	180	50	400	Ball bearing	25	60
ALEV 200/20K	200	50	450	Ball bearing	20	60
ALEV 200/25K	200	50	450	Ball bearing	25	60
ALEV 250/20K	250	50	550	Ball bearing	20	60
ALEV 250/25K	250	50	550	Ball bearing	25	60

7

Further information on the internet: www.blickle.de

Variants / Accessories



	With non-marking grey tyre	Antistatic version, black tyre
Technical description page	37	37
Ref. No. extension	-SG	-EL
Available for wheel Ø [mm]	All sizes	Upon request

