

Series: L-ALEV, B-ALEV, BH-ALEV

Pressed steel swivel and fixed castors, medium duty brackets

180 - 550 kg



Brackets: L/B/BH Series - Pressed steel, swivel bracket with double ball bearing in the reinforced swivel head, dynamically pressed in accordance with special Blickle procedure resulting in an extremely low swivel head play and a long service life, strong central kingpin (wheel Ø 150-250 mm) and swivel head sealing, bolted wheel axle, zinc-plated.

Wheels: ALEV Series - Tyres: Elastic solid rubber, smooth rolling quality, colour black, 65° shore A, vulcanised, non-detachable connection, low rolling resistance. Wheel centres: Made of aluminium die-cast, corrosion-resistant, ball bearing, colour aluminium.


Top plate drawings: Page 71.
Detailed description: Page 62 and 76.

7

Swivel castors	Fixed castors	Swivel castors with "stop-fix" brake
----------------	---------------	--------------------------------------

Ref. No.	Ref. No.	Ref. No.	Wheel Ø [mm]	Tyre width [mm]	Load capacity [kg]	Bearing version	Total height [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
L-ALEV 100K	B-ALEV 100K	L-ALEV 100K-FI	100	40	180	Ball bearing	125	100 x 85	80 x 60	9	36
L-ALEV 125K	B-ALEV 125K	L-ALEV 125K-FI	125	40	200	Ball bearing	150	100 x 85	80 x 60	9	40
L-ALEV 150K	B-ALEV 150K	L-ALEV 150K-FI	150	54	350	Ball bearing	190	140 x 110	105 x 75-80	11	60
L-ALEV 161K	B-ALEV 161K	L-ALEV 161K-FI	160	40	300	Ball bearing	195	140 x 110	105 x 75-80	11	60
L-ALEV 160K	B-ALEV 160K	L-ALEV 160K-FI	160	50	350	Ball bearing	195	140 x 110	105 x 75-80	11	60
L-ALEV 180K	B-ALEV 180K	L-ALEV 180K-FI	180	50	400	Ball bearing	215	140 x 110	105 x 75-80	11	60
L-ALEV 200K	B-ALEV 200K	L-ALEV 200K-FI	200	50	400	Ball bearing	235	140 x 110	105 x 75-80	11	65
L-ALEV 250K-3	BH-ALEV 250K	*	250	50	550	Ball bearing	295	140 x 110	105 x 75-80	11	77

* For the "stop-top" brake version, refer to Variants / Accessories.



Further information on the internet: www.blickle.de

Variants / Accessories



	With non-marking grey tyre	Antistatic version, black tyre	With "stop-top" brake	With directional lock (retro fit)** 1 x 360°
Technical description page	37	37	77	78
Ref. No. extension	-SG	-EL	-ST	RI-05.03
Available for wheel Ø [mm]	All sizes	Upon request	All sizes	160 - 200

** Only for swivel castors without brake.