

Series: LO-ALEV, BO-ALEV

Welded steel heavy duty swivel and fixed castors

270 - 550 kg



Brackets: LO/BO Series - Heavy welded steel construction, swivel bracket with double ball bearing in the swivel head, additionally reinforced by the integration of four specially shaped and hardened bearing seats, labyrinth swivel head sealing with grease nipple, welded very strong, bolted and secured central kingpin, bolted wheel axle, zinc-plated.

Wheels: ALEV Series - Tyres: Elastic solid rubber, smooth rolling quality, colour black, 65° shore A, vulcanised, non-detachable connection, low rolling resistance. Wheel centres: Made of aluminium die-cast, corrosion-resistant, ball bearing, colour aluminium.

Detailed description: Page 161 and 37.

Top plate drawings: Page 71.
Detailed description: Page 64 and 77.

7


Swivel castors

Fixed castors

Swivel castors with "stop-top" brake

Ref. No.	Ref. No.	Ref. No.	Wheel Ø [mm]	Tyre width [mm]	Load capacity [kg]	Bearing version	Total height [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
LO-ALEV 127K	BO-ALEV 127K	LO-ALEV 127K-ST	125	50	270	Ball bearing	170	140 x 110	105 x 75-80	11	50
LO-ALEV 150K	BO-ALEV 150K	LO-ALEV 150K-ST	150	54	350	Ball bearing	200	140 x 110	105 x 75-80	11	55
LO-ALEV 160K	BO-ALEV 160K	LO-ALEV 160K-ST	160	50	350	Ball bearing	205	140 x 110	105 x 75-80	11	55
LO-ALEV 200K	BO-ALEV 200K	LO-ALEV 200K-ST	200	50	450	Ball bearing	245	140 x 110	105 x 75-80	11	60
LO-ALEV 250K	BO-ALEV 250K	LO-ALEV 250K-ST	250	50	550	Ball bearing	295	140 x 110	105 x 75-80	11	70

Further information on the internet: www.blickle.de



Variants / Accessories



	With non-marking grey tyre	Antistatic version, black tyre	With directional lock 2 x 180°
Technical description page	37	37	78
Ref. No. extension	-SG	-EL	-RI2
Available for wheel Ø [mm]	All sizes	Upon request	125 - 200