

Series: LK-SE, BK-SE, BH-SE

Pressed steel swivel and fixed castors, medium heavy duty brackets

180 - 500 kg



Brackets: LK/BK/BH Series - Pressed from heavy sheet-steel, swivel bracket with double ball bearing in the reinforced swivel head, dynamically pressed in accordance with special Blickle procedure resulting in an extremely low swivel head play and a long service life, strong central kingpin (wheel Ø 125-200 mm) and swivel head sealing, bolted wheel axle, zinc-plated.


Wheels: SE Series - Tyres: Elastic solid rubber, smooth rolling quality, colour black, 65° shore A, vulcanised, non-detachable connection, low rolling resistance. Wheel centres: Strong welded steel construction with double-welded tubular steel hub or, for wheel Ø of 100+125 mm, direct vulcanisation of elastic solid rubber tyres onto the hub, ball bearing. Lacquered - colour anthracite.

Top plate drawings: Page 71.
Detailed description: Page 63 and 76.

Special Blickle wheel centre construction, very high stability, elegant and smooth design.
Detailed description: Page 168 and 37.

Swivel castors	Fixed castors	Swivel castors with "stop-fix" brake
----------------	---------------	--------------------------------------

Ref. No.	Ref. No.	Ref. No.	Wheel Ø [mm]	Tyre width [mm]	Load capacity [kg]	Bearing version	Total height [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
LK-SE 100K-1	BK-SE 100K-1	LK-SE 100K-1-FI	100	40	180	Ball bearing	130	100 x 85	80 x 60	9	45
LK-SE 100K-3	BK-SE 100K-3	LK-SE 100K-3-FI	100	40	180	Ball bearing	130	140 x 110	105 x 75-80	11	45
LK-SE 125K	BH-SE 125K	LK-SE 125K-FI	125	50	280	Ball bearing	170	140 x 110	105 x 75-80	11	55
LK-SE 160K	BH-SE 160K	LK-SE 160K-FI	160	50	400	Ball bearing	202	140 x 110	105 x 75-80	11	63
LK-SE 200K	BH-SE 200K	LK-SE 200K-FI	200	50	500	Ball bearing	245	140 x 110	105 x 75-80	11	65



Variants / Accessories



	With non-marking grey tyre	With "stop-top" brake	With "ideal-stop" brake ttd. height +17mm*	With directional lock (retro fit)** 1 x 360°	With directional lock (retro fit)** 1 x 360°
Technical description page	37	77	77	78	78
Ref. No. extension	-SG	-ST	-IS	RI-03.03	RI-05.03
Available for wheel Ø [mm]	160 - 200	All sizes	160 + 200	100 plate 140x110	125 - 200

* Matching synthetic adapter plate for total height compensation for swivel and fixed castors without "ideal-stop" brake: Ref. No. AP3.
** Only for swivel castors without brake.