

Series: LH-SE, BH-SE

**Pressed steel swivel and fixed castors, heavy duty brackets**

180 - 700 kg



**Brackets:** LH/BH Series - Pressed from sheet-steel, swivel bracket with heavy fork and top plate, very strong bolted and secured central kingpin, double ball bearing in the swivel head, additionally reinforced by the integration of four specially shaped and hardened bearing seats resulting in a very high resistance to shock and impact loads, bolted wheel axle, zinc-plated.

Top plate drawings: Page 71.  
Detailed description: Page 63 and 76.

**Wheels:** SE Series - Tyres: Elastic solid rubber, smooth rolling quality, colour black, 65° shore A, vulcanised, non-detachable connection, low rolling resistance. Wheel centres: Strong welded steel construction with double-welded tubular steel hub or, for wheel Ø of 100+125 mm, direct vulcanisation of elastic solid rubber tyres onto the hub, ball bearing. Lacquered - colour anthracite.

**Special Blickle wheel centre construction, very high stability, elegant and smooth design.**  
Detailed description: Page 168 and 37.

7

Swivel castors	Fixed castors	Swivel castors with "stop-fix" brake
----------------	---------------	--------------------------------------

Ref. No.	Ref. No.	Ref. No.	Wheel Ø [mm]	Tyre width [mm]	Load capacity [kg]	Bearing version	Total height [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
LH-SE 100K-1	BH-SE 100K-1	LH-SE 100K-1-FI	100	40	180	Ball bearing	140	100 x 85	80 x 60	9	45
LH-SE 100K-3		LH-SE 100K-3-FI	100	40	180	Ball bearing	140	140 x 110	105 x 75-80	11	45
LH-SE 125K	BH-SE 125K	LH-SE 125K-FI	125	50	280	Ball bearing	170	140 x 110	105 x 75-80	11	55
LH-SE 160K	BH-SE 160K	LH-SE 160K-FI	160	50	400	Ball bearing	202	140 x 110	105 x 75-80	11	65
LH-SE 200K	BH-SE 200K	LH-SE 200K-FI	200	50	500	Ball bearing	245	140 x 110	105 x 75-80	11	70
LH-SE 202K		*	200	80	700	Ball bearing	245	140 x 110	105 x 75-80	11	70
LH-SE 250K	BH-SE 250K	*	250	60	700	Ball bearing	295	140 x 110	105 x 75-80	11	82

\* For the "stop-top" brake version, refer to Variants / Accessories.



Further information on the internet: [www.blickle.de](http://www.blickle.de)

**Variants / Accessories**



	With non-marking grey tyre	With "stop-top" brake	With "ideal-stop" brake ttl. height + 17mm**	With directional lock (retro fit)*** 1 x 360°	With sealing + grease nipple in the swivel head ***	Truck lock
Technical description page	37	77	77	78	63	78
Ref. No. extension	-SG	-ST	-IS	RI-05.03	-DN	FF160 / FF200
Available for wheel Ø [mm]	160 - 200	All sizes	160 + 200x50	125 - 200x50	Upon request	160 - 200 Rest upon request

\*\* Matching synthetic adapter plate for total height compensation for swivel and fixed castors without "ideal-stop" brake: Ref. No. AP3.

\*\*\* Only for swivel castors without brake.