

Series: LO-SE, BO-SE

Welded steel heavy duty swivel and fixed castors

 280 - 900 kg




Brackets: LO/BO Series - Heavy welded steel construction, swivel bracket with double ball bearing in the swivel head, additionally reinforced by the integration of four specially shaped and hardened bearing seats, labyrinth swivel head sealing with grease nipple, welded very strong, bolted and secured central kingpin, bolted wheel axle, zinc-plated.

Top plate drawings: Page 71.
Detailed description: Page 64 and 77.

Wheels: SE Series - Tyres: Elastic solid rubber, smooth rolling quality, colour black, 65° shore A, vulcanised, non-detachable connection, low rolling resistance. Wheel centres: Strong welded steel construction with double-welded tubular steel hub or, for wheel Ø of 125 mm, direct vulcanisation of elastic solid rubber tyres onto the hub, ball bearing. Lacquered - colour anthracite. **Special Blickle wheel centre construction, very high stability, elegant and smooth design.** Detailed description: Page 168 and 37.

Swivel castors	Fixed castors	Swivel castors with "stop-top" brake	Wheel Ø [mm]	Tyre width [mm]	Load capacity [kg]	Bearing version	Total height [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
Ref. No.	Ref. No.	Ref. No.									
LO-SE 125K	BO-SE 125K	LO-SE 125K-ST	125	50	280	Ball bearing	170	140 x 110	105 x 75-80	11	50
LO-SE 160K	BO-SE 160K	LO-SE 160K-ST	160	50	400	Ball bearing	205	140 x 110	105 x 75-80	11	55
LO-SE 200K	BO-SE 200K	LO-SE 200K-ST	200	50	500	Ball bearing	245	140 x 110	105 x 75-80	11	60
LO-SE 202K	BO-SE 202K	LO-SE 202K-ST	200	80	700	Ball bearing	245	140 x 110	105 x 75-80	11	65
LO-SE 250K	BO-SE 250K	LO-SE 250K-ST	250	60	700	Ball bearing	295	140 x 110	105 x 75-80	11	70
LO-SE 252K	BO-SE 252K	LO-SE 252K-ST	250	80	850	Ball bearing	295	140 x 110	105 x 75-80	11	70
LO-SE 300K	BO-SE 300K	LO-SE 300K-ST	300	75	900	Ball bearing	350	140 x 110	105 x 75-80	11	75



7
Further information on the internet: www.blickle.de

Variants / Accessories



	With non-marking grey tyre	With plate size 175 x 140 mm	With directional lock 2 x 180°	Truck lock
Technical description page	37	72	78	78
Ref. No. extension	-SG	-35	-RI2	FF160 / FF200
Available for wheel Ø [mm]	160 - 200	Upon request	125 - 200x50	160 - 200 Rest upon request