

Series: LS-SE, BS-SE

**Welded steel heavy duty
swivel and fixed castors,
extra strong swivel head design**

👤 280 - 1150 kg



Brackets: LS/BS Series - Very rugged welded steel construction, swivel bracket with axial grooved ball bearing DIN 711 and tapered roller bearing DIN 720 in the swivel head, dust and splash-proof. Fitted grease nipple, welded very strong, bolted and secured central kingpin, bolted wheel axle, zinc-plated - yellow passivated.
Top plate drawings: Page 71 and 72.
Detailed description: Page 64 and 77.


Wheels: SE Series - Tyres: Elastic solid rubber, smooth rolling quality, colour black, 65° shore A, vulcanised, non-detachable connection, low rolling resistance.
Ref. No. ...-Z: Pressed-on.
Wheel centres: Strong welded steel construction with double-welded tubular steel hub or, for wheel Ø of 125 mm, direct vulcanisation of elastic solid rubber tyres onto the hub, ball bearing, lacquered - colour anthracite.
Special Blickle wheel centre construction, very high stability, elegant and smooth design.
Detailed description: Page 168 and 37.

7

Swivel castors Fixed castors Swivel castors with "stop-top" brake

Ref. No.	Ref. No.	Ref. No.	Wheel Ø [mm]	Tyre width [mm]	Load capacity [kg]	Bearing version	Total height [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
LS-SE 125K	BS-SE 125K	LS-SE 125K-ST	125	50	280	Ball bearing	170	140 x 110	105 x 75-80	11	50
LS-SE 160K	BS-SE 160K	LS-SE 160K-ST	160	50	400	Ball bearing	205	140 x 110	105 x 75-80	11	55
LS-SE 200K	BS-SE 200K	LS-SE 200K-ST	200	50	500	Ball bearing	245	140 x 110	105 x 75-80	11	60
LS-SE 202K	BS-SE 202K	LS-SE 202K-ST	200	80	700	Ball bearing	255	175 x 140	140 x 105	14	65
LS-SE 250K	BS-SE 250K	LS-SE 250K-ST	250	60	700	Ball bearing	305	175 x 140	140 x 105	14	75
LS-SE 252K	BS-SE 252K	LS-SE 252K-ST	250	80	850	Ball bearing	305	175 x 140	140 x 105	14	75
LS-SE 300K	BS-SE 300K	LS-SE 300K-ST	300	75	900	Ball bearing	355	175 x 140	140 x 105	14	85
LS-SE 360K-Z	BS-SE 360K-Z		360	75	950	Ball bearing	420	175 x 140	140 x 105	14	100
LS-SE 415K-Z	BS-SE 415K-Z		415	90	1150	Ball bearing	478	200 x 160	160 x 120	14	100

Further information on the internet: www.blickle.de



Variants / Accessories



	With non-marking grey tyre	With directional lock 2 x 180°	With directional lock 4 x 90°	Truck lock
Technical description page	37	78	78	78
Ref. No. extension	-SG	-RI2	-RI4	FF160 / FF200
Available for wheel Ø [mm]	160 - 200	All sizes	Upon request	160 - 200 Rest upon request