

Series: LSD-SE, BSD-SE

**Welded steel heavy duty
double swivel and fixed castors,
extra strong swivel head design**

👤 800 - 1800 kg




Swivel castors **Fixed castors**

Brackets: LSD/BSL Series - Very rugged welded steel construction, swivel bracket with axial grooved ball bearing DIN 711 and tapered roller bearing DIN 720 in the swivel head, dust and splash-proof. Fitted grease nipple, welded very strong, bolted and secured central kingpin, bolted wheel axle.
Wheel Ø 160+200 mm: Zinc-plated - yellow passivated.
Wheel Ø 250+300 mm: Lacquered - colour red.
Top plate drawings: Page 72.
Detailed description: Page 64.

Wheels: SE Series - Tyres: Elastic solid rubber, smooth rolling quality, colour black, 65° shore A, vulcanised, non-detachable connection, low rolling resistance.
Wheel centres: Strong welded steel construction with double-welded tubular steel hub, ball bearing. Lacquered - colour anthracite.
Special Blickle wheel centre construction, very high stability, elegant and smooth design.
Detailed description: Page 168 and 37.

Ref. No.	Ref. No.	Wheel Ø [mm]	Tyre width [mm]	Load capacity [kg]	Bearing version	Total height [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
LSD-SE 160K-35	BSD-SE 160K-35	160	2 x 50	800	Ball bearing	220	140 x 175*	105 x 140	14	55
LSD-SE 200K-35	BSD-SE 200K-35	200	2 x 50	1000	Ball bearing	260	140 x 175*	105 x 140	14	60
LSD-SE 250K	BSD-SE 250K	250	2 x 60	1400	Ball bearing	330	200 x 255*	160 x 210	18	70
LSD-SE 300K	BSD-SE 300K	300	2 x 75	1800	Ball bearing	380	200 x 255*	160 x 210	18	80

* Fixed castors: Long plate side in parallel with the wheel axle



Variants / Accessories

	With "Radstop" wheel brake	With directional lock
Technical description page	78	78
Ref. No. extension	-RA	
Available for wheel Ø [mm]	Upon request	Upon request