

Series: DS

**Heavy duty double wheels
with elastic solid rubber tyres,
welded steel wheel centre, heavy design**

 1500 - 6000 kg



Tyres: Fitted two elastic solid rubber tyres, smooth rolling quality, colour black, 65° shore A, steel-wire reinforced, pressed-on, low rolling resistance.

Wheel centres: Very strong welded steel construction double-welded tubular steel hub, ball bearing, fitted grease nipple.

Lacquered - colour anthracite.

Detailed description: Page 37 and 39.

Wheels

Ref. No.	Wheel Ø (D) [mm]	Tyre width (T2) [mm]	Load capacity [kg]	Bearing version	Axle bore Ø (d) [mm]	Hub length (T1) [mm]
DS 300/50K	300	150 (2 x 75)	1500	Ball bearing	50	150
DS 302/55K	300	180 (2 x 90)	1800	Ball bearing	55	180
DS 361/50K	360	150 (2 x 75)	1900	Ball bearing	50	150
DS 400/55K	400	150 (2 x 75)	2000	Ball bearing	55	150
DS 405/75K	405	260 (2 x 130)	3000	Ball bearing	75	250
DS 415/60K	415	180 (2 x 90)	2300	Ball bearing	60	180
DS 425/80K	425	300 (2 x 150)	3600	Ball bearing	80	250
DS 500/60K	500	170 (2 x 85)	2600	Ball bearing	60	170
DS 620/100K	620	400 (2 x 200)	6000	Ball bearing	100	300

7

Further information on the internet: www.blickle.de

Variants / Accessories



	With steel-band tyre in drive quality	Wheel with hub cap (end wheel)	Further dimensions
Technical description page	37 - 39	79	
Ref. No. extension	-SBA	-E	
Available for wheel Ø [mm]	Upon request	Upon request	Upon request

