

Series: SAV

**Heavy duty hub fitting wheels  
with elastic solid rubber tyres,  
welded steel wheel centre**

**525 - 3000 kg**



**Tyres:** Elastic solid rubber, drive quality, colour black, 65° shore A, steel-wire reinforced, pressed-on.  
**Wheel centres:** Very strong welded steel construction, central piece with counter-sunk fitting holes for counter-sunk nuts or screws.  
Lacquered - colour anthracite.  
Detailed description: Page 37 and 39.

7

Further information on the internet: [www.blickle.de](http://www.blickle.de)

**Wheels**

Ref. No.	Wheel Ø (D) [mm]	Tyre width (T2) [mm]	Load capacity [kg]	Rim fitting dimensions:			
				No. of holes	Fitting hole Ø (d2) [mm]	Central hole Ø (d) [mm]	Hole circle Ø (d1) [mm]
SAV 250/4	250	60	525	4	16,5	60	100
SAV 252/4	250	80	675	4	16,5	60	100
SAV 300/4	300	75	750	4	16,5	60	100
SAV 300/5	300	75	750	5	16,5	67	112
SAV 302/4	300	90	900	4	16,5	60	100
SAV 302/5	300	90	900	5	16,5	67	112
SAV 360/4	360	60	750	4	16,5	60	100
SAV 360/5	360	60	750	5	16,5	67	112
SAV 362/4	360	75	950	4	16,5	60	100
SAV 362/5-67	360	75	950	5	16,5	67	112
SAV 362/5-82	360	75	950	5	16,5	82	130
SAV 400/4	400	65	900	4	16,5	60	100
SAV 400/5-67	400	65	900	5	16,5	67	112
SAV 400/5-82	400	65	900	5	16,5	82	130
SAV 402/4	400	75	1000	4	16,5	60	100
SAV 402/5-67	400	75	1000	5	16,5	67	112
SAV 402/5-82	400	75	1000	5	16,5	82	130
SAV 405/5	405	130	1500	5	18,5	110	145
SAV 405/6	405	130	1500	6	21,5	160	205
SAV 415/5	415	90	1150	5	18,5	110	145
SAV 415/6	415	90	1150	6	21,5	160	205
SAV 500/6	500	85	1300	6	21,5	160	205
SAV 520/6	520	100	1525	6	21,5	160	205
SAV 620/6	620	200	3000	6	21,5	160	205

**Variants / Accessories**



With steel-band tyre  
in drive quality

Further dimensions

Technical description page	37 - 39	
Ref. No. extension	-SBA	
Available for wheel Ø [mm]	Upon request	Upon request

