

Series: L-P, B-P

Pressed steel swivel and fixed castors, medium duty brackets

75 - 250 kg



Brackets: L/B Series - Pressed steel, swivel bracket with double ball bearing in the reinforced swivel head, dynamically pressed in accordance with special Blickle procedure resulting in an extremely low swivel head play and a long service life, strong central kingpin and swivel head sealing (except for brackets with 175x175 mm plate), bolted wheel axle, zinc-plated.

Wheels: P Series - Tyres: Pneumatic tyres with ribbed or zig-zag profile, 2 or 4 ply rating, with tube.
Rims: Pressed steel, bolted or welded, welded tubular steel hub, roller bearing, zinc-plated.
Detailed description: Page 182 and 40.

Top plate drawings: Page 71.
Detailed description: Page 62 and 77.

8

Further information on the internet: www.blickle.de

Swivel castors	Fixed castors	Swivel castors with "stop-top" brake
----------------	---------------	--------------------------------------

Ref. No.	Ref. No.	Ref. No.	Wheel Ø [mm]	Tyre width [mm]	Load capacity [kg]	Bearing version	Total height [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
L-P 200R*	B-P 200R*	L-P 200R-ST*	200	50	75	Roller bearing	235	140 x 110	105 x 75-80	11	65
L-P 220R*	B-P 220R*	L-P 220R-ST*	220	65	100	Roller bearing	250	140 x 110	105 x 75-80	11	67
L-P 222R	B-P 222R	L-P 222R-ST	220	65	100	Roller bearing	250	140 x 110	105 x 75-80	11	67
L-P 261R*	B-P 261R*	L-P 261R-ST*	260	85	150	Roller bearing	308	175 x 175	140 x 140	15	78
L-P 263R		L-P 263R-ST	260	85	150	Roller bearing	308	220 x 120	190 x 75	15	78
L-P 265R*	B-P 265R*	L-P 265R-ST*	260	85	250	Roller bearing	308	175 x 175	140 x 140	15	78
L-P 267R		L-P 267R-ST	260	85	250	Roller bearing	308	220 x 120	190 x 75	15	78
	B-P 267R		260	85	250	Roller bearing	308	175 x 175	140 x 140	15	78
			260	85	250	Roller bearing	308	220 x 120	190 x 75	15	78

* Ribbed profile



Variants / Accessories



	With non-marking grey tyre	With puncture-proof, foam-filled tyre	With directional lock (retro fit)** 1 x 360°	Castors with puncture-proof soft rubber wheels
Technical description page	40	40	78	35
Ref. No. extension	-SG	-AG	RI-05.03	
Available for wheel Ø [mm]	All sizes	Upon request	200	Refer to page 147.

** Only for swivel castors without brake.