

Series: PK  
**Wheels with pneumatic tyres,  
synthetic rim**

75 - 250 kg



**Tyres:** Pneumatic tyres with ribbed or zig-zag profile, 2 ply rating, with tube.  
**Rims:** Made of polypropylene, shock and impact-resistant, corrosion-resistant, plain, roller or ball bearing, colour black.  
Detailed description: Page 41.

**Ribbed profile**

**Zig-zag profile**

Ref. No.	Ref. No.	Wheel Ø (D) [mm]	Tyre width (T2) [mm]	Tyre dimension	Ply rating	Load capacity [kg]	Tyre pressure [bar/psi]	Bearing version	Axle bore Ø (d) [mm]	Hub length (T1) [mm]
PK 200/20-60G		200	50	200x50	2	75	2,5/36	Plain bearing	20	60
PK 260/20-75G	PK 257/20-75G*	260	85	3.00-4	2	150	2,0/30	Plain bearing	20	75
PK 260/25-75G	PK 262/20-75G	260	85	3.00-4	2	150	2,0/30	Plain bearing	20	75
PK 260/20-75R	PK 262/25-75G	260	85	3.00-4	2	150	2,0/30	Plain bearing	25	75
PK 260/25-75R	PK 262/20-75R	260	85	3.00-4	2	150	2,0/30	Roller bearing	20	75
PK 260/25-75R	PK 262/25-75R	260	85	3.00-4	2	150	2,0/30	Roller bearing	25	75
PK 260/20-75K	PK 262/20-75K	260	85	3.00-4	2	150	2,0/30	Ball bearing	20	75
PK 300/20-75G	PK 302/20-75G	300	100	4.00-4	2	180	2,0/30	Plain bearing	20	75
PK 300/25-75G	PK 302/25-75G	300	100	4.00-4	2	180	2,0/30	Plain bearing	25	75
PK 300/20-75R	PK 302/20-75R	300	100	4.00-4	2	180	2,0/30	Roller bearing	20	75
PK 300/25-75R	PK 302/25-75R	300	100	4.00-4	2	180	2,0/30	Roller bearing	25	75
PK 300/20-75K	PK 302/20-75K	300	100	4.00-4	2	180	2,0/30	Ball bearing	20	75
PK 400/20-75G	PK 402/20-75G	400	100	4.00-8	2	250	2,0/30	Plain bearing	20	75
PK 400/25-75G	PK 402/25-75G	400	100	4.00-8	2	250	2,0/30	Plain bearing	25	75
PK 400/20-75R	PK 402/20-75R	400	100	4.00-8	2	250	2,0/30	Roller bearing	20	75
PK 400/25-75R	PK 402/25-75R	400	100	4.00-8	2	250	2,0/30	Roller bearing	25	75

\* Reduced profile depth

8

Further information on the internet: [www.blickle.de](http://www.blickle.de)

**Variants / Accessories**



	With non-marking grey tyre	With puncture-proof, foam-filled tyre	Red centre	Puncture-proof soft rubber wheels
Technical description page	41	41	41	35
Ref. No. extension	-SG	-AG	-ROT	
Available for wheel Ø [mm]	200 - 260	Upon request	260 - 400	Refer to page 148.

