



Series: PA

Hub fitting wheels with pneumatic tyres, pressed steel rim

100 - 1300 kg



Wheels

Tyres: Pneumatic tyres with zig-zag profile, 2 - 10 ply rating, with tube.
Rims: Pressed steel, bolted or welded, with impressed or counter-sunk fitting holes for counter-sunk nuts or screws.
 Wheel Ø 400 - 415 mm:
 Lacquered - colour silver.
 Wheel Ø 420 - 536 mm: zinc-plated.

With a reduced load capacity, max. speeds of up to 25 km/h are permissible, refer to the table.

Detailed description: Page 41.

8

Further information on the internet: www.blickle.de

| Ref. No. | Wheel Ø (D) [mm] | Tyre width (T2) [mm] | Tyre dimension | Ply rating | Load cap. with 4 km/h [kg] | Load cap. with 25 km/h [kg] | Tyre pressure [bar/psi] | Rim fitting dimensions: No. of holes | Fitting hole Ø (d2) [mm] | Central hole Ø (d) [mm] | Hole circle Ø (d1) [mm] |
|----------|------------------|----------------------|----------------|------------|----------------------------|-----------------------------|-------------------------|--------------------------------------|--------------------------|-------------------------|-------------------------|
| PA 402/4 | 400 | 100 | 4.00-8 | 2 | 250 | 100 | 2,0/30 | 4 | 14,5 | 60 | 100 |
| PA 412/4 | 400 | 100 | 4.00-8 | 4 | 350 | 160 | 3,5/50 | 4 | 14,5 | 60 | 100 |
| PA 420/4 | 415 | 115 | 4.00-8 | 4 | 525 | 300 | 3,5/50 | 4 | 14,5 | 60 | 100 |
| PA 430/5 | 420 | 115 | 4.00-8 | 6 | 650 | 500 | 7,0/101 | 5 | 16,5 | 82 | 130 |
| PA 432/5 | 420 | 115 | 4.00-8 | 8 | 750 | 600 | 7,0/101 | 5 | 16,5 | 82 | 130 |
| PA 464/5 | 460 | 145 | 5.00-8 | 8 | 1140 | 770 | 7,0/101 | 5 | 16,5 | 82 | 130 |
| PA 536/5 | 536 | 165 | 6.00-9 | 10 | 1300 | 1050 | 7,0/101 | 5 | 16,5 | 110 | 145 |

Variants / Accessories



Further fitting dimensions

Technical description page

Ref. No. extension

Available for wheel Ø [mm] Upon request

