

Series: PTH

**Wheels with polyurethane tread,
nylon wheel centre**

 125 - 500 kg



Treads: Made of injection-moulded polyurethane, colour grey, non-marking, 98° shore A, abrasion-resistant, non-staining, floor-saving, low-noise operation, low rolling resistance, excellent positive and non-positive connection with the wheel centre.

Wheel centres: Made of high-quality nylon, colour light grey, shock and impact-resistant, corrosion-resistant, plain, roller or ball bearing.

Detailed description: Page 43.

Wheels

Ref. No.	Wheel Ø (D) [mm]	Wheel width (T2) [mm]	Load capacity [kg]	Bearing version	Axle bore Ø (d) [mm]	Hub length (T1) [mm]
PTH 80/12G	80	30	125	Plain bearing	12	35
PTH 80/12R	80	30	125	Roller bearing	12	35
PTH 100/12G	100	30	150	Plain bearing	12	45
PTH 100/12R	100	30	150	Roller bearing	12	45
PTH 100/15R	100	30	150	Roller bearing	15	45
PTH 100/8K	100	30	150	Ball bearing	8	46
PTH 100/10K	100	30	150	Ball bearing	10	46
PTH 125/12G	125	30	180	Plain bearing	12	45
PTH 125/12R	125	30	180	Roller bearing	12	45
PTH 125/15R	125	30	180	Roller bearing	15	45
PTH 125/8K	125	30	180	Ball bearing	8	46
PTH 125/10K	125	30	180	Ball bearing	10	46
PTH 160/20G	160	40	400	Plain bearing	20	60
PTH 160/20R	160	40	400	Roller bearing	20	60
PTH 160/20K	160	40	400	Ball bearing	20	60
PTH 200/20G	200	50	500	Plain bearing	20	60
PTH 200/20R	200	50	400	Roller bearing	20	60
PTH 200/20K	200	50	500	Ball bearing	20	60

10

Further information on the internet: www.blickle.de

Variants / Accessories



	Antistatic version, non-marking grey	With stainless steel roller bearing	With stainless steel ball bearing
Technical description page	43	57	57
Ref. No. extension	-ELS	-XR	-XK
Available for wheel Ø [mm]	Upon request	All sizes	Upon request

