

Series: L-PTH, B-PTH

## Pressed steel swivel and fixed castors, medium duty brackets

 125 - 400 kg




**Brackets:** L/B Series - Pressed steel, swivel bracket with double ball bearing in the reinforced swivel head, dynamically pressed in accordance with special Blickle procedure resulting in an extremely low swivel head play and a long service life, strong central kingpin (wheel Ø 160+200 mm) and swivel head sealing, bolted wheel axle, zinc-plated.

**Wheels:** PTH Series - Treads: Made of injection-moulded polyurethane, colour grey, non-marking, 98° shore A, abrasion-resistant, non-staining, floor-saving, low-noise operation, low rolling resistance, excellent positive and non-positive connection with the wheel centre. Wheel centres: Made of high-quality nylon, colour light grey, shock and impact-resistant, corrosion-resistant, plain, roller or ball bearing.

Top plate drawings: Page 71.  
Detailed description: Page 62 and 76.

Swivel castors	Fixed castors	Swivel castors with "stop-fix" brake
----------------	---------------	--------------------------------------

Ref. No.	Ref. No.	Ref. No.	Wheel Ø [mm]	Wheel width [mm]	Load capacity [kg]	Bearing version	Total height [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
L-PTH 80G	B-PTH 80G	L-PTH 80G-FI	80	30	125	Plain bearing	102	100 x 85	80 x 60	9	38
L-PTH 80R	B-PTH 80R	L-PTH 80R-FI	80	30	125	Roller bearing	102	100 x 85	80 x 60	9	38
L-PTH 100R	B-PTH 100R	L-PTH 100R-FI	100	30	150	Roller bearing	125	100 x 85	80 x 60	9	36
L-PTH 100K	B-PTH 100K	L-PTH 100K-FI	100	30	150	Ball bearing	125	100 x 85	80 x 60	9	36
L-PTH 125R	B-PTH 125R	L-PTH 125R-FI	125	30	180	Roller bearing	150	100 x 85	80 x 60	9	40
L-PTH 125K	B-PTH 125K	L-PTH 125K-FI	125	30	180	Ball bearing	150	100 x 85	80 x 60	9	40
L-PTH 160R	B-PTH 160R	L-PTH 160R-FI	160	40	400	Roller bearing	195	140 x 110	105 x 75-80	11	60
L-PTH 160K	B-PTH 160K	L-PTH 160K-FI	160	40	400	Ball bearing	195	140 x 110	105 x 75-80	11	60
L-PTH 200R	B-PTH 200R	L-PTH 200R-FI	200	50	400	Roller bearing	235	140 x 110	105 x 75-80	11	65
L-PTH 200K	B-PTH 200K	L-PTH 200K-FI	200	50	400	Ball bearing	235	140 x 110	105 x 75-80	11	65



### Variants / Accessories



	Antistatic version, non-marking grey	With pressed steel thread guard, zinc-plated	With "stop-top" brake	With directional lock (retro fit)* 1 x 360°	With stainless steel roller bearing in the wheel hub	With stainless steel ball bearing in the wheel hub
Technical description page	43	79	77	78	57	57
Ref. No. extension	-ELS	-FA	-ST	RI-05.03	-XR	-XK
Available for wheel Ø [mm]	Upon request	All sizes	All sizes	160 + 200	All sizes	Upon request

\* Only for swivel castors without brake.