

Series: POTH

**Wheels with polyurethane tread,
heavy nylon wheel centre**

 150 - 700 kg



Treads: Made of injection-moulded polyurethane, colour brown, non-marking, 98° shore A, non-staining, abrasion-resistant, floor-saving, low-noise operation, low rolling resistance, excellent positive and non-positive connection with the wheel centre.

Wheel centres: Made of high-quality nylon, colour natural white, shock and impact-resistant, corrosion-resistant, plain, roller or ball bearing. Detailed description: Page 43.

Alternatively available with soft tread with improved skid resistance, colour grey, 92° shore A, refer to Variants / Accessories.

Wheels

Ref. No.	Wheel Ø (D) [mm]	Wheel width (T2) [mm]	Load capacity [kg]	Bearing version	Axle bore Ø (d) [mm]	Hub length (T1) [mm]
POTH 75/15G	75	37	150	Plain bearing	15	45
POTH 75/15R	75	37	150	Roller bearing	15	45
POTH 100/12G	100	35	200	Plain bearing	12	45
POTH 100/15G	100	35	200	Plain bearing	15	45
POTH 100/12R	100	35	200	Roller bearing	12	45
POTH 100/15R	100	35	200	Roller bearing	15	45
POTH 100/10K	100	35	200	Ball bearing	10	46
POTH 125/12G	125	35	250	Plain bearing	12	45
POTH 125/15G	125	35	250	Plain bearing	15	45
POTH 125/12R	125	35	250	Roller bearing	12	45
POTH 125/15R	125	35	250	Roller bearing	15	45
POTH 125/10K	125	35	250	Ball bearing	10	46
POTH 125/15K	125	35	250	Ball bearing	15	45
POTH 150/20G	150	40	400	Plain bearing	20	60
POTH 150/20R	150	40	400	Roller bearing	20	60
POTH 150/20K	150	40	400	Ball bearing	20	60
POTH 200/20G	200	50	700	Plain bearing	20	60
POTH 200/20R	200	50	400	Roller bearing	20	60
POTH 200/20K	200	50	700	Ball bearing	20	60
POTH 200/25K	200	50	700	Ball bearing	25	60

10

Further information on the internet: www.blickle.de

Variants / Accessories



	With soft tread, 92° shore A, non-marking grey	With stainless steel roller bearing	With stainless steel ball bearing
Technical description page	43	57	57
Ref. No. extension	-WE	-XR	-XK
Available for wheel Ø [mm]	Upon request	All sizes	Upon request

