

Series: L-ALST, B-ALST, BH-ALST
**Pressed steel swivel and fixed castors,
medium duty brackets**

200 - 600 kg



Brackets: L/BH Series - Pressed steel, swivel bracket with double ball bearing in the reinforced swivel head, dynamically pressed in accordance with special Blickle procedure resulting in an extremely low swivel head play and a long service life, strong central kingpin (wheel Ø 160-250 mm) and swivel head sealing, bolted wheel axle, zinc-plated.


Top plate drawings: Page 71.
Detailed description: Page 62 and 76.

Wheels: ALST Series - Treads: Made of Blickle Softhane® polyurethane, firmly bonded, colour green, non-marking, **very high operational comfort because of particularly thick, elastic tread**, 75° shore A, abrasion-resistant, high cut and tear propagation resistance, non-staining, floor-saving, low-noise operation, low rolling resistance, very good chemical connection with the wheel centre. Wheel centres: Made of aluminium die-cast, corrosion-resistant, ball bearing, colour aluminium. Detailed description: Page 210 and 44.

Swivel castors	Fixed castors	Swivel castors with "stop-fix" brake
----------------	---------------	--------------------------------------

Ref. No.	Ref. No.	Ref. No.	Wheel Ø [mm]	Wheel width [mm]	Load capacity [kg]	Bearing version	Total height [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
L-ALST 100K	B-ALST 100K	L-ALST 100K-FI	100	40	200	Ball bearing	125	100 x 85	80 x 60	9	36
L-ALST 125K	B-ALST 125K	L-ALST 125K-FI	125	40	200	Ball bearing	150	100 x 85	80 x 60	9	40
L-ALST 160K	B-ALST 160K	L-ALST 160K-FI	160	50	400	Ball bearing	195	140 x 110	105 x 75-80	11	60
L-ALST 200K	B-ALST 200K	L-ALST 200K-FI	200	50	400	Ball bearing	235	140 x 110	105 x 75-80	11	65
L-ALST 250K-3	BH-ALST 250K	*	250	50	600	Ball bearing	295	140 x 110	105 x 75-80	11	77

* For the "stop-top" brake version, refer to Variants / Accessories.



Variants / Accessories



	With "stop-top" brake	With directional lock (retro fit)** 1 x 360°
Technical description page	77	78
Ref. No. extension	-ST	RI-05.03
Available for wheel Ø [mm]	All sizes	160 + 200

** Only for swivel castors without brake.