

Series: LK-ALST, BK-ALST, BH-ALST

Pressed steel swivel and fixed castors, medium heavy duty brackets

250 - 600 kg



Brackets: LK/BK/BH Series - Pressed from heavy sheet-steel, swivel bracket with double ball bearing in the reinforced swivel head, dynamically pressed in accordance with special Blickle procedure resulting in an extremely low swivel head play and a long service life, strong central kingpin (wheel Ø 160+200 mm) and swivel head sealing, bolted wheel axle, zinc-plated.

Top plate drawings: Page 71.
Detailed description: Page 63 and 76.

Wheels: ALST Series - Treads: Made of Blickle Softhane® polyurethane, firmly bonded, colour green, non-marking, **very high operational comfort because of particularly thick, elastic tread**, 75° shore A, abrasion-resistant, high cut and tear propagation resistance, non-staining, floor-saving, low-noise operation, low rolling resistance, very good chemical connection with the wheel centre. Wheel centres: Made of aluminium die-cast, corrosion-resistant, ball bearing, colour aluminium. Detailed description: Page 210 and 44.

Swivel castors


Fixed castors

Swivel castors with "stop-fix" brake

Ref. No.	Ref. No.	Ref. No.	Wheel Ø [mm]	Wheel width [mm]	Load capacity [kg]	Bearing version	Total height [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
LK-ALST 100K-1	BK-ALST 100K-1	LK-ALST 100K-1-FI	100	40	250	Ball bearing	130	100 x 85	80 x 60	9	45
LK-ALST 100K-3	BK-ALST 100K-3	LK-ALST 100K-3-FI	100	40	250	Ball bearing	130	140 x 110	105 x 75-80	11	45
LK-ALST 125K-1	BK-ALST 125K-1	LK-ALST 125K-1-FI	125	40	250	Ball bearing	155	100 x 85	80 x 60	9	48
LK-ALST 125K-3	BK-ALST 125K-3	LK-ALST 125K-3-FI	125	40	250	Ball bearing	155	140 x 110	105 x 75-80	11	48
LK-ALST 160K	BH-ALST 160K	LK-ALST 160K-FI	160	50	550	Ball bearing	202	140 x 110	105 x 75-80	11	63
LK-ALST 200K	BH-ALST 200K	LK-ALST 200K-FI	200	50	600	Ball bearing	245	140 x 110	105 x 75-80	11	65

11

Further information on the internet: www.blickle.de



Variants / Accessories



	With "stop-top" brake	With "ideal-stop" brake ttl. height +17mm*	With directional lock (retro fit)** 1 x 360°	With directional lock (retro fit)** 1 x 360°
Technical description page	77	77	78	78
Ref. No. extension	-ST	-IS	RI-03.03	RI-05.03
Available for wheel Ø [mm]	All sizes	160 + 200	100 + 125 plate 140x110	160 + 200

* Matching synthetic adapter plate for total height compensation for swivel and fixed castors without "ideal-stop" brake: Ref. No. AP3.
** Only for swivel castors without brake.