

Series: LKR-ALST

**Pressed steel swivel castors  
with bolt hole fitting,  
medium heavy duty brackets**

 250 kg



**Brackets:** LKR Series - Pressed from heavy sheet-steel, single bolt hole fitting, double ball bearing in the swivel head, dynamically pressed in accordance with special Blickle procedure resulting in an extremely low swivel head play and a long service life, strong central kingpin, bolted wheel axle, zinc-plated.  
Detailed description: Page 63 and 76.

**Wheels:** ALST Series - Treads: Made of Blickle Softhane® polyurethane, firmly bonded, colour green, non-marking, **very high operational comfort because of particularly thick, elastic tread**, 75° shore A, abrasion-resistant, high cut and tear propagation resistance, non-staining, floor-saving, low-noise operation, low rolling resistance, very good chemical connection with the wheel centre. Wheel centres: Made of aluminium die-cast, corrosion-resistant, ball bearing, colour aluminium.  
Detailed description: Page 210 and 44.

**Swivel castors**      **Swivel castors  
with "stop-fix"  
brake**

Ref. No.	Ref. No.	Wheel Ø [mm]	Wheel width [mm]	Load capacity [kg]	Bearing version	Total height [mm]	Plate Ø [mm]	Bolt hole Ø [mm]	Offset [mm]
LKR-ALST 100K	LKR-ALST 100K-FI	100	40	250	Ball bearing	130	88	13	45
LKR-ALST 125K	LKR-ALST 125K-FI	125	40	250	Ball bearing	155	88	13	48

