

Series: LH-ALST, BH-ALST

Pressed steel swivel and fixed castors, heavy duty brackets

300 - 800 kg



Brackets: LH/BH Series - Pressed from sheet-steel, swivel bracket with heavy fork and top plate, very strong bolted and secured central kingpin, double ball bearing in the swivel head, additionally reinforced by the integration of four specially shaped and hardened bearing seats resulting in a very high resistance to shock and impact loads, bolted wheel axle, zinc-plated.

Wheels: ALST Series - Treads: Made of Blickle Softhane® polyurethane, firmly bonded, colour green, non-marking, very high operational comfort because of particularly thick, elastic tread, 75° shore A, abrasion-resistant, high cut and tear propagation resistance, non-staining, floor-saving, low-noise operation, low rolling resistance, very good chemical connection with the wheel centre. Wheel centres: Made of aluminium die-cast, corrosion-resistant, ball bearing, colour aluminium. Detailed description: Page 210 and 44.

Top plate drawings: Page 71.
Detailed description: Page 63 and 76.

Swivel castors	Fixed castors	Swivel castors with "stop-fix" brake	Wheel Ø [mm]	Wheel width [mm]	Load capacity [kg]	Bearing version	Total height [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
LH-ALST 100K-1	BH-ALST 100K-1	LH-ALST 100K-1-FI	100	40	300	Ball bearing	140	100 x 85	80 x 60	9	45
LH-ALST 100K-3		LH-ALST 100K-3-FI	100	40	300	Ball bearing	140	140 x 110	105 x 75-80	11	45
LH-ALST 125K-1	BH-ALST 125K-1	LH-ALST 125K-1-FI	125	40	350	Ball bearing	165	100 x 85	80 x 60	9	45
LH-ALST 125K-3	BH-ALST 125K-3	LH-ALST 125K-3-FI	125	40	350	Ball bearing	165	140 x 110	105 x 75-80	11	45
LH-ALST 160K	BH-ALST 160K	LH-ALST 160K-FI	160	50	550	Ball bearing	202	140 x 110	105 x 75-80	11	65
LH-ALST 200K	BH-ALST 200K	LH-ALST 200K-FI	200	50	700	Ball bearing	245	140 x 110	105 x 75-80	11	70
LH-ALST 250K	BH-ALST 250K	*	250	50	800	Ball bearing	295	140 x 110	105 x 75-80	11	82

* For the "stop-top" brake version, refer to Variants / Accessories.

11

Further information on the internet: www.blickle.de



Variants / Accessories



	With "stop-top" brake	With "ideal-stop" brake ttl. height + 17mm**	With directional lock (retro fit)*** 1 x 360°	With sealing + grease nipple in the swivel head ***
Technical description page	77	77	78	63
Ref. No. extension	-ST	-IS	RI-05.03	-DN
Available for wheel Ø [mm]	All sizes	160 + 200	160 + 200	Upon request

** Matching synthetic adapter plate for total height compensation for swivel and fixed castors without "ideal-stop" brake: Ref. No. AP3.
*** Only for swivel castors without brake.