

Series: LO-ALST, BO-ALST

**Welded steel heavy duty  
swivel and fixed castors**

 550 - 800 kg




**Brackets:** LO/BO Series - Heavy welded steel construction, swivel bracket with double ball bearing in the swivel head, additionally reinforced by the integration of four specially shaped and hardened bearing seats, labyrinth swivel head sealing with grease nipple, welded very strong, bolted and secured central kingpin, bolted wheel axle, zinc-plated.

Top plate drawings: Page 71.  
Detailed description: Page 64 and 77.

**Wheels:** ALST Series - Treads: Made of Blickle Softhane® polyurethane, firmly bonded, colour green, non-marking, very high operational comfort because of particularly thick, elastic tread, 75° shore A, abrasion-resistant, high cut and tear propagation resistance, non-staining, floor-saving, low-noise operation, low rolling resistance, very good chemical connection with the wheel centre. Wheel centres: Made of aluminium die-cast, corrosion-resistant, ball bearing, colour aluminium. Detailed description: Page 210 and 44.

Swivel castors	Fixed castors	Swivel castors with "stop-top" brake
----------------	---------------	--------------------------------------

Ref. No.	Ref. No.	Ref. No.	Wheel Ø [mm]	Wheel width [mm]	Load capacity [kg]	Bearing version	Total height [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
LO-ALST 160K	BO-ALST 160K	LO-ALST 160K-ST	160	50	550	Ball bearing	205	140 x 110	105 x 75-80	11	55
LO-ALST 200K	BO-ALST 200K	LO-ALST 200K-ST	200	50	700	Ball bearing	245	140 x 110	105 x 75-80	11	60
LO-ALST 250K	BO-ALST 250K	LO-ALST 250K-ST	250	50	800	Ball bearing	295	140 x 110	105 x 75-80	11	70



**Variants / Accessories**



With directional lock  
2 x 180°

Technical description page	78
Ref. No. extension	-RI2
Available for wheel Ø [mm]	160 + 200