

Series: ALTH

**Heavy duty wheels  
with Blickle Extrathane® polyurethane tread,  
aluminium wheel centre**

**180 - 1000 kg**



**Treads:** Made of Blickle Extrathane® polyurethane, firmly bonded, colour light brown, non-marking, 92° shore A, elastic, abrasion-resistant, high cut and tear propagation resistance, non-staining, floor-saving, low-noise operation, low rolling resistance, very good chemical connection with the wheel centre.

**Wheel centres:** Made of aluminium die-cast, corrosion-resistant, ball bearing, colour aluminium.  
Detailed description: Page 44.

**Wheels**

Ref. No.	Wheel Ø (D) [mm]	Wheel width (T2) [mm]	Load capacity [kg]	Bearing version	Axle bore Ø (d) [mm]	Hub length (T1) [mm]
ALTH 80/15K	80	30	180	Ball bearing	15	35
ALTH 100/15K	100	40	250	Ball bearing	15	45
ALTH 101/15K*	100	40	350	Ball bearing	15	40
ALTH 125/15K	125	40	350	Ball bearing	15	45
ALTH 127/20K	125	54	450	Ball bearing	20	60
ALTH 140/20K	140	54	500	Ball bearing	20	60
ALTH 150/20K	150	50	500	Ball bearing	20	60
ALTH 160/20K	160	50	550	Ball bearing	20	60
ALTH 180/20K	180	50	600	Ball bearing	20	60
ALTH 200/20K	200	50	800	Ball bearing	20	60
ALTH 200/25K	200	50	800	Ball bearing	25	60
ALTH 250/25K	250	60	1000	Ball bearing	25	70

\* heavy design

12

Further information on the internet: [www.blickle.de](http://www.blickle.de)

**Variants / Accessories**



Antistatic version,  
non-marking grey

Technical description page	44
Ref. No. extension	-AS
Available for wheel Ø [mm]	Upon request

