

Series: LKR-ALTH

Pressed steel swivel castors with bolt hole fitting, medium heavy duty brackets

 180 - 250 kg



Brackets: LKR Series - Pressed from heavy sheet-steel, single bolt hole fitting, double ball bearing in the swivel head, dynamically pressed in accordance with special Blickle procedure resulting in an extremely low swivel head play and a long service life, strong central kingpin, bolted wheel axle, zinc-plated.
Detailed description: Page 63 and 76.

Wheels: ALTH Series - Treads: Made of Blickle Extrathane® polyurethane, firmly bonded, colour light brown, non-marking, 92° shore A, elastic, abrasion-resistant, high cut and tear propagation resistance, non-staining, floor-saving, low-noise operation, low rolling resistance, very good chemical connection with the wheel centre.
Wheel centres: Made of aluminium die-cast, corrosion-resistant, ball bearing, colour aluminium.
Detailed description: Page 218 and 44.

Swivel castors

Swivel castors with "stop-fix" brake

Ref. No.	Ref. No.	Wheel Ø [mm]	Wheel width [mm]	Load capacity [kg]	Bearing version	Total height [mm]	Plate Ø [mm]	Bolt hole Ø [mm]	Offset [mm]
LKR-ALTH 80K		80	30	180	Ball bearing	110	88	13	40
LKR-ALTH 100K	LKR-ALTH 100K-FI	100	40	250	Ball bearing	130	88	13	45
LKR-ALTH 125K	LKR-ALTH 125K-FI	125	40	250	Ball bearing	155	88	13	48



Variants / Accessories



Antistatic version, non-marking grey

Technical description page

44

Ref. No. extension

-AS

Available for wheel Ø [mm]

Upon request