


Series: SETH

**Heavy duty wheels
with Blickle Extrathane[®] polyurethane tread,
welded steel wheel centre**

 500 - 1350 kg



Treads: Made of Blickle Extrathane[®] polyurethane, firmly bonded, colour light brown, non-marking, 92° shore A, elastic, abrasion-resistant, high cut and tear propagation resistance, non-staining, floor-saving, low-noise operation, low rolling resistance, very good chemical connection with the wheel centre.

Wheel centres: Strong welded steel construction with double-welded tubular steel hub, ball bearing. Lacquered - colour silver.

This special Blickle wheel centre construction is characterised by its particularly high stability as well as its elegant and smooth design.

Detailed description: Page 45.

Wheels

Ref. No.	Wheel Ø (D) [mm]	Wheel width (T2) [mm]	Load capacity [kg]	Bearing version	Axle bore Ø (d) [mm]	Hub length (T1) [mm]
SETH 125/20K	125	50	500	Ball bearing	20	60
SETH 150/20K	150	50	650	Ball bearing	20	60
SETH 150/25K	150	50	650	Ball bearing	25	60
SETH 160/20K	160	50	700	Ball bearing	20	60
SETH 160/25K	160	50	700	Ball bearing	25	60
SETH 200/20K	200	50	1000	Ball bearing	20	60
SETH 200/25K	200	50	1000	Ball bearing	25	60
SETH 250/25K	250	60	1350	Ball bearing	25	70

12

Further information on the internet: www.blickle.de

Variants / Accessories



With grease nipple

Technical description page	45
Ref. No. extension	-NI
Available for wheel Ø [mm]	Upon request

