

Series: LO-SETH, BO-SETH

Welded steel heavy duty swivel and fixed castors

 500 - 1200 kg



Brackets: LO/BO Series - Heavy welded steel construction, swivel bracket with double ball bearing in the swivel head, additionally reinforced by the integration of four specially shaped and hardened bearing seats, labyrinth swivel head sealing with grease nipple, welded very strong, bolted and secured central kingpin, bolted wheel axle, zinc-plated.

Top plate drawings: Page 71.
Detailed description: Page 64 and 77.

Wheels: SETH Series - Treads: Made of Blickle Extrathane® polyurethane, firmly bonded, colour light brown, non-marking, 92° shore A, elastic, abrasion-resistant, high cut and tear propagation resistance, non-staining, floor-saving, low-noise operation, low rolling resistance, very good chemical connection with the wheel centre. Wheel centres: Strong welded steel construction with double-welded tubular steel hub, ball bearing. Lacquered - colour silver.
Special Blickle wheel centre construction, very high stability, elegant and smooth design.
Detailed description: Page 224 and 45.


Swivel castors

Fixed castors

Swivel castors with "stop-top" brake

Ref. No.	Ref. No.	Ref. No.	Wheel Ø [mm]	Wheel width [mm]	Load capacity [kg]	Bearing version	Total height [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
LO-SETH 125K	BO-SETH 125K	LO-SETH 125K-ST	125	50	500	Ball bearing	170	140 x 110	105 x 75-80	11	50
LO-SETH 150K	BO-SETH 150K	LO-SETH 150K-ST	150	50	650	Ball bearing	200	140 x 110	105 x 75-80	11	55
LO-SETH 160K	BO-SETH 160K	LO-SETH 160K-ST	160	50	700	Ball bearing	205	140 x 110	105 x 75-80	11	55
LO-SETH 200K	BO-SETH 200K	LO-SETH 200K-ST	200	50	1000	Ball bearing	245	140 x 110	105 x 75-80	11	60
LO-SETH 250K	BO-SETH 250K	LO-SETH 250K-ST	250	60	1200	Ball bearing	295	140 x 110	105 x 75-80	11	70

12



Further information on the internet: www.blickle.de



Variants / Accessories

	With directional lock 2 x 180°	Truck lock
Technical description page	78	78
Ref. No. extension	-RI2	FF160 / FF200
Available for wheel Ø [mm]	125 - 200	160 - 200 Rest upon request