

Series: LO-GTH, BO-GTH

**Welded steel heavy duty swivel and fixed castors**

 550 - 1250 kg



**Brackets:** LO/BO Series - Heavy welded steel construction, swivel bracket with double ball bearing in the swivel head, additionally reinforced by the integration of four specially shaped and hardened bearing seats, labyrinth swivel head sealing with grease nipple, welded very strong, bolted and secured central kingpin, bolted wheel axle, zinc-plated.

Top plate drawings: Page 71.  
Detailed description: Page 64 and 77.


**Wheels:** GTH Series - Treads: Made of Blickle Extrathane® polyurethane, firmly bonded, colour light brown, non-marking, 92° shore A, elastic, abrasion-resistant, high cut and tear propagation resistance, non-staining, floor-saving, low-noise operation, low rolling resistance, very good chemical connection with the wheel centre. Wheel centres: Made of grey cast iron, very rugged, ball bearing, grease nipple for wheel Ø of 150 mm or larger. Lacquered - colour silver. Detailed description: Page 228, 229 and 45.

**Swivel castors**

**Fixed castors**

**Swivel castors with "stop-top" brake**

Ref. No.	Ref. No.	Ref. No.	Wheel Ø [mm]	Wheel width [mm]	Load capacity [kg]	Bearing version	Total height [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
LO-GTH 127K	BO-GTH 127K	LO-GTH 127K-ST	125	50	550	Ball bearing	170	140 x 110	105 x 75-80	11	50
LO-GTH 150K	BO-GTH 150K	LO-GTH 150K-ST	150	50	700	Ball bearing	200	140 x 110	105 x 75-80	11	55
LO-GTH 160K	BO-GTH 160K	LO-GTH 160K-ST	160	50	750	Ball bearing	205	140 x 110	105 x 75-80	11	55
LO-GTH 200K	BO-GTH 200K	LO-GTH 200K-ST	200	50	1000	Ball bearing	245	140 x 110	105 x 75-80	11	60
LO-GTH 202K	BO-GTH 202K	LO-GTH 202K-ST	200	80	1250	Ball bearing	245	140 x 110	105 x 75-80	11	65
LO-GTH 251K	BO-GTH 251K	LO-GTH 251K-ST	250	50	1100	Ball bearing	295	140 x 110	105 x 75-80	11	70
LO-GTH 250K	BO-GTH 250K	LO-GTH 250K-ST	250	60	1200	Ball bearing	295	140 x 110	105 x 75-80	11	70
LO-GTH 301K	BO-GTH 301K	LO-GTH 301K-ST	300	45	1100	Ball bearing	350	140 x 110	105 x 75-80	11	75



**Variants / Accessories**



	With plate size 175 x 140 mm	With directional lock 2 x 180°	Truck lock
Technical description page	72	78	78
Ref. No. extension	-35	-RI2	FF160 / FF200
Available for wheel Ø [mm]	Upon request	125 - 200x50	160 - 200 Rest upon request